


室内灯具光度数据

实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm		
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

光源数据		光度数据				光效: 11.74 lm/W
型号	2835	峰值光强(cd)	32.81	S/MH(C0/180)	1.24	
标称功率(W)		灯具效率(%)	100.0	S/MH(C90/270)	1.26	
额定电源电压(V)	24	总光通量(lm)	100.56	η UP,DN(C0-180)	1.9,48.0	
额定光通量(lm)	100.555	CIE分类	直接	η UP,DN(C180-360)	1.8,48.3	
灯具内光源数(只)	1	上射光通比(%)	3.7	CIBSE SHR NOM	1.25	
实测电源电压(V)		下射光通比(%)	96.3	CIBSE SHR MAX	1.35	



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-14

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

灯具环带光通量

环带光通量：

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ(°)	Φ环	Φ总	%lum, lamp
10	32.25	32.25	32.18	32.13	32.13	32.17	32.25	32.29	0- 10	3.103	3.103	3.09,3.09
20	30.49	30.51	30.43	30.31	30.28	30.38	30.52	30.59	10- 20	8.879	11.98	11.9,11.9
30	27.67	27.70	27.61	27.44	27.41	27.53	27.72	27.81	20- 30	13.43	25.41	25.3,25.3
40	23.99	24.00	23.89	23.69	23.68	23.82	24.04	24.16	30- 40	16.18	41.59	41.4,41.4
50	19.65	19.65	19.53	19.31	19.31	19.45	19.69	19.84	40- 50	16.82	58.41	58.1,58.1
60	14.91	14.91	14.79	14.55	14.57	14.70	14.94	15.11	50- 60	15.39	73.80	73.4,73.4
70	10.02	10.00	9.886	9.653	9.689	9.802	10.02	10.21	60- 70	12.24	86.04	85.6,85.6
80	5.145	5.093	4.963	4.754	4.818	4.906	5.107	5.303	70- 80	7.869	93.91	93.4,93.4
90	1.092	0.8521	0.4923	0.7434	0.9160	0.7884	0.5178	0.9511	80- 90	2.932	96.85	96.3,96.3
100	0.4503	0.4780	0.5155	0.4857	0.4191	0.4740	0.5184	0.4764	90-100	0.5651	97.41	96.9,96.9
110	0.4959	0.5179	0.5445	0.5322	0.4647	0.5179	0.5676	0.5162	100-110	0.5258	97.94	97.4,97.4
120	0.5501	0.5640	0.5880	0.5817	0.5217	0.5625	0.5966	0.5570	110-120	0.5388	98.47	97.9,97.9
130	0.5986	0.6042	0.6372	0.6296	0.5758	0.6114	0.6285	0.6006	120-130	0.5271	99.00	98.5,98.5
140	0.6471	0.6488	0.6836	0.6776	0.6357	0.6617	0.6718	0.6413	130-140	0.4904	99.49	98.9,98.9
150	0.6955	0.7035	0.7501	0.7300	0.6927	0.7078	0.7095	0.6907	140-150	0.4287	99.92	99.4,99.4
160	0.7411	0.7639	0.8052	0.7766	0.7469	0.7524	0.7501	0.7416	150-160	0.3395	100.3	99.7,99.7
170	0.7733	0.7998	0.8196	0.8048	0.7867	0.7927	0.7906	0.7934	160-170	0.2203	100.5	99.9,99.9
180	0.7896	0.8114	0.8254	0.8173	0.7924	0.8114	0.8196	0.8173	170-180	0.0766	100.6	100,100
单位:°	光强:cd									单位:lm		

锥面光通量(90度)：50.053 lm


%lum = 49.8%
%lamp = 49.8%

锥面光通量(130度)：80.407 lm

%lum = 80.0%
%lamp = 80.0%

灯具亮度限制曲线

实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm		
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



平均亮度值 cd/(m2)		
γ (°)	C0/180	C90/270
85	2386	2110
80	2222	2110
75	2196	2119
70	2197	2134
65	2215	2157
60	2237	2184
55	2263	2212
50	2292	2243
45	2321	2274


C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-14

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

工作面利用系数和灯具概算曲线

实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm		
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	工 作 面 利 用 系 数															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.04	1.04	1.04	.99	.99	.99	.96
1.0	1.02	.98	.94	.00	.95	.92	.95	.91	.88	.90	.87	.85	.86	.84	.82	.79
2.0	.89	.82	.76	.86	.80	.74	.82	.77	.72	.78	.74	.70	.75	.71	.68	.65
3.0	.78	.69	.62	.76	.68	.62	.72	.66	.60	.69	.63	.59	.66	.61	.57	.55
4.0	.69	.60	.53	.67	.59	.52	.64	.57	.51	.61	.55	.50	.59	.53	.49	.47
5.0	.61	.52	.45	.60	.51	.45	.57	.50	.44	.55	.48	.43	.53	.47	.42	.40
6.0	.55	.46	.39	.54	.45	.39	.52	.44	.38	.50	.43	.38	.48	.42	.37	.35
7.0	.50	.41	.35	.49	.40	.34	.47	.39	.34	.45	.38	.33	.43	.38	.33	.31
8.0	.45	.37	.31	.45	.36	.31	.43	.36	.30	.41	.35	.30	.40	.34	.29	.28
9.0	.42	.33	.28	.41	.33	.28	.39	.32	.27	.38	.32	.27	.37	.31	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.35	.29	.24	.34	.28	.24	.22



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-14

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

墙面和天花板利用系数

实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm					
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R			灯具类型:		灯具重量:
灯具规格:			外型尺寸: Length=1m		测试编号:
制造厂商: OLympia lighting			发光口面:		遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	墙 壁 面 利 用 系 数															
0.0																
1.0	.325	.185	.059	.317	.181	.057	.302	.173	.055	.288	.166	.053	.275	.159	.051	
2.0	.301	.165	.051	.293	.162	.050	.280	.156	.048	.267	.150	.047	.255	.144	.046	
3.0	.276	.147	.044	.269	.144	.043	.257	.139	.042	.246	.135	.041	.235	.130	.040	
4.0	.253	.131	.039	.247	.129	.038	.236	.125	.037	.226	.121	.037	.217	.118	.036	
5.0	.233	.119	.034	.228	.117	.034	.218	.114	.033	.209	.110	.033	.200	.107	.032	
6.0	.215	.108	.031	.211	.106	.031	.202	.104	.030	.194	.101	.030	.186	.098	.029	
7.0	.200	.099	.028	.196	.098	.028	.188	.095	.027	.181	.093	.027	.174	.090	.027	
8.0	.187	.091	.026	.183	.090	.025	.176	.088	.025	.169	.086	.025	.163	.084	.024	
9.0	.175	.084	.024	.171	.083	.023	.165	.081	.023	.159	.080	.023	.153	.078	.022	
10.0	.164	.079	.022	.161	.078	.022	.155	.076	.021	.150	.074	.021	.144	.073	.021	

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	天花板利用系数															
0.0	.219	.219	.219	.187	.187	.187	.128	.128	.128	.073	.073	.073	.023	.023	.023	
1.0	.210	.184	.161	.179	.158	.139	.123	.109	.096	.071	.063	.056	.023	.020	.018	
2.0	.202	.160	.125	.173	.138	.108	.119	.096	.076	.068	.056	.044	.022	.018	.014	
3.0	.194	.143	.102	.167	.123	.089	.114	.086	.062	.066	.050	.037	.021	.016	.012	
4.0	.187	.130	.087	.160	.112	.075	.110	.078	.053	.064	.046	.031	.020	.015	.010	
5.0	.179	.120	.076	.154	.103	.066	.106	.072	.047	.061	.042	.028	.020	.014	.009	
6.0	.172	.111	.068	.148	.096	.059	.102	.067	.042	.059	.040	.025	.019	.013	.008	
7.0	.165	.105	.062	.142	.091	.054	.098	.064	.038	.057	.037	.023	.018	.012	.008	
8.0	.158	.099	.058	.136	.086	.050	.094	.060	.036	.055	.035	.021	.018	.012	.007	
9.0	.152	.094	.054	.131	.081	.047	.091	.057	.034	.053	.034	.020	.017	.011	.007	
10.0	.147	.090	.052	.126	.078	.045	.088	.055	.032	.051	.032	.019	.017	.011	.006	

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度: 25.3℃ 测试人员: 测试日期: 2025-03-14	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度: 65.0% 测试距离: 6.360米 [K=1.0000] 备注:
--	---

UGR(Unified Glare Rating)数据表

实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm												
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R						灯具类型:			灯具重量:			
灯具规格:						外型尺寸: Length=1m			测试编号:			
制造厂商: OLympia lighting						发光口面:			遮光角:			
反射比:		天花板	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
		墙面	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
		工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
房间尺寸			横向(Viewed crosswise)					纵向(Viewed endwise)				
x = 2H y = 2H	2H	22.7	24.2	23.0	24.5	24.8	22.6	24.1	22.9	24.4	24.6	
	3H	24.4	25.8	24.8	26.1	26.4	24.3	25.7	24.6	26.0	26.3	
	4H	25.2	26.5	25.5	26.8	27.1	25.0	26.3	25.4	26.7	27.0	
	6H	25.8	27.1	26.2	27.4	27.8	25.6	26.9	26.0	27.2	27.6	
	8H	26.1	27.3	26.5	27.6	28.0	25.9	27.1	26.3	27.4	27.8	
	12H	26.3	27.4	26.7	27.8	28.2	26.0	27.2	26.5	27.6	27.9	
4H	2H	23.3	24.7	23.7	25.0	25.3	23.3	24.6	23.6	24.9	25.2	
	3H	25.3	26.4	25.7	26.8	27.2	25.1	26.3	25.5	26.7	27.0	
	4H	26.2	27.2	26.6	27.6	28.0	26.0	27.1	26.5	27.5	27.9	
	6H	26.9	27.9	27.4	28.3	28.8	26.8	27.7	27.2	28.1	28.6	
	8H	27.3	28.1	27.7	28.6	29.0	27.1	28.0	27.6	28.4	28.9	
	12H	27.5	28.3	28.0	28.8	29.3	27.3	28.1	27.8	28.6	29.1	
8H	4H	26.5	27.4	27.0	27.8	28.3	26.4	27.2	26.8	27.7	28.1	
	6H	27.5	28.2	28.0	28.7	29.2	27.3	28.0	27.8	28.5	29.0	
	8H	27.9	28.6	28.4	29.1	29.6	27.7	28.4	28.2	28.9	29.4	
	12H	28.3	28.9	28.8	29.4	29.9	28.1	28.6	28.6	29.1	29.7	
12H	4H	26.5	27.3	27.0	27.8	28.3	26.4	27.2	26.9	27.7	28.1	
	6H	27.6	28.2	28.1	28.7	29.2	27.4	28.1	27.9	28.6	29.1	
	8H	28.1	28.6	28.6	29.1	29.7	27.9	28.4	28.4	29.0	29.5	
不同间隔布灯时,观察者位置引起的UGR变化(CIE Pub.117):												
S = 1.0H		+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H		+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H		+ 0.1 / - 0.3					+ 0.1 / - 0.3					

依据CIE Pub.117计算, 100.6lm光源光通表格中的数据需要进行修正(8log(F/F0) = -8.0).
出光口面积: 0.0135 m2

C角度范围: 0度 - 360度	γ角度范围: 0度 - 180度
C角度间隔: 30.0度	γ角度间隔: 1.0度
测试速度: 快速	测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境温度:25.3℃	环境湿度:65.0%
测试人员:	测试距离:6.360米 [K=1.0000]
测试日期:2025-03-14	备注:

UF利用系数表

实测参数：U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通：100.555x1 lm		
灯具名称：SF10-24V-5050-84-SPI-RGBW(2700K)-R	灯具类型：	灯具重量：
灯具规格：	外型尺寸：Length=1m	测试编号：
制造厂商：OLympia lighting	发光口面：	遮光角：


反 射 比 / REFLECTANCE										
天花板	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
墙壁	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
室形指数	利用系数 UTILIZATION FACTORS(%) k(RI) x RCR = 5									
k = 0.60	56	44	37	55	44	37	53	43	36	30
0.80	65	54	46	64	53	46	62	52	45	38
1.00	74	62	55	72	62	54	70	63	54	46
1.25	81	70	62	79	69	62	76	67	61	53
1.50	86	75	68	84	74	68	80	72	66	58
2.00	93	84	77	91	82	76	87	80	74	65
2.50	97	89	82	94	87	81	90	84	79	69
3.00	100	93	87	98	91	86	93	88	83	74
4.00	104	98	93	102	96	92	97	92	88	78
5.00	107	102	97	104	99	95	99	95	92	81
ROOM INDEX	UF (总)									UF (直接)
依据标准文件 DIN EN 13032-2 2004			悬挂灯				安装距高比 SHR _{NOM} = 1.25			

C角度范围： 0度 - 360度
C角度间隔：30.0度
测试速度：快速
环境温度:25.3℃
测试人员：
测试日期:2025-03-14

γ角度范围： 0度 - 180度
γ角度间隔： 1.0度
测试系统：远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注：

灯 具 等 光 强 曲 线

实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm		
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-14

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

灯 具 有 效 平 均 照 度 图

实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm		
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-14

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

平面等照度曲线

实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm		
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-14

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

LED筒灯平均亮度报告


实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm		
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

平均亮度	数值 (cd/m2)
L横 (65) av	2158
L横 (75) av	2121
L横 (85) av	2227
L纵 (65) av	2177
L纵 (75) av	2145
L纵 (85) av	2188
L45 (65) av	2169
L45 (75) av	2135
L45 (85) av	2202

注:依据标准 GB/T 29293-2012 计算

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度:25.3℃ 测试人员: 测试日期:2025-03-14	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注:
--	---

平面照度曲线



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-14

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

光 强 分 布 数 据 表 格

实测参数: U:24.00V I:0.3568A P:8.563W PF:1.000 Freq:0Hz 实检光通: 100.555x1 lm																	
灯具名称: SF10-24V-5050-84-SPI-RGBW(2700K)-R									灯具类型:						灯具重量:		
灯具规格:									外型尺寸: Length=1m						测试编号:		
制造厂商: OLympia lighting									发光口面:						遮光角:		


表--1单位: cd

C (DEG) γ (DEG)	0	30	60	90	120	150	180	210	240	270	300	330						
0	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8	32.8						
5	32.7	32.7	32.7	32.6	32.6	32.6	32.6	32.6	32.6	32.7	32.7	32.7						
10	32.2	32.3	32.2	32.2	32.1	32.1	32.1	32.1	32.2	32.2	32.3	32.3						
15	31.5	31.5	31.5	31.4	31.4	31.3	31.3	31.4	31.5	31.5	31.6	31.6						
20	30.5	30.5	30.5	30.4	30.3	30.3	30.3	30.3	30.4	30.5	30.6	30.6						
25	29.2	29.2	29.2	29.1	29.0	29.0	29.0	29.0	29.2	29.2	29.3	29.3						
30	27.7	27.7	27.7	27.6	27.5	27.4	27.4	27.4	27.6	27.7	27.8	27.8						
35	25.9	26.0	25.9	25.9	25.7	25.6	25.6	25.7	25.9	26.0	26.1	26.1						
40	24.0	24.0	24.0	23.9	23.7	23.7	23.7	23.7	23.9	24.0	24.2	24.1						
45	21.9	21.9	21.8	21.8	21.6	21.5	21.6	21.6	21.8	21.9	22.1	22.0						
50	19.6	19.7	19.6	19.5	19.3	19.3	19.3	19.3	19.6	19.7	19.9	19.8						
55	17.3	17.4	17.3	17.2	17.0	16.9	17.0	17.0	17.2	17.4	17.5	17.5						
60	14.9	15.0	14.9	14.8	14.6	14.5	14.6	14.6	14.8	14.9	15.1	15.1						
65	12.5	12.5	12.4	12.3	12.1	12.1	12.1	12.1	12.4	12.5	12.7	12.6						
70	10.0	10.1	9.94	9.89	9.67	9.64	9.69	9.70	9.91	10.02	10.2	10.2						
75	7.58	7.61	7.48	7.43	7.21	7.19	7.24	7.25	7.44	7.56	7.76	7.73						
80	5.14	5.17	5.02	4.96	4.76	4.75	4.82	4.82	5.00	5.11	5.31	5.30						
85	2.77	2.76	2.56	2.49	2.31	2.38	2.47	2.43	2.55	2.66	2.86	2.87						
90	1.09	1.00	0.71	0.49	0.64	0.85	0.92	0.87	0.71	0.52	0.83	1.07						
95	0.45	0.46	0.48	0.50	0.47	0.46	0.39	0.43	0.48	0.50	0.49	0.44						
100	0.45	0.48	0.47	0.52	0.48	0.49	0.42	0.44	0.51	0.52	0.51	0.44						
105	0.47	0.51	0.49	0.53	0.50	0.51	0.44	0.45	0.54	0.54	0.53	0.46						
110	0.50	0.53	0.51	0.54	0.52	0.54	0.46	0.48	0.56	0.57	0.55	0.48						
115	0.53	0.55	0.53	0.57	0.55	0.57	0.49	0.50	0.58	0.58	0.57	0.50						
120	0.55	0.58	0.55	0.59	0.58	0.59	0.52	0.53	0.60	0.60	0.60	0.52						
125	0.58	0.61	0.56	0.61	0.60	0.61	0.54	0.55	0.62	0.62	0.61	0.55						
130	0.60	0.62	0.59	0.64	0.62	0.64	0.58	0.58	0.64	0.63	0.63	0.57						
135	0.62	0.64	0.61	0.66	0.64	0.67	0.60	0.61	0.66	0.65	0.66	0.59						
140	0.65	0.66	0.64	0.68	0.67	0.69	0.64	0.63	0.69	0.67	0.67	0.61						
145	0.67	0.68	0.67	0.72	0.70	0.72	0.66	0.66	0.71	0.69	0.69	0.64						
150	0.70	0.71	0.70	0.75	0.72	0.74	0.69	0.68	0.73	0.71	0.71	0.67						
155	0.72	0.73	0.74	0.78	0.74	0.77	0.72	0.71	0.75	0.74	0.74	0.69						
160	0.74	0.75	0.77	0.81	0.76	0.79	0.75	0.73	0.77	0.75	0.77	0.72						
165	0.76	0.78	0.79	0.82	0.78	0.80	0.78	0.76	0.79	0.77	0.78	0.74						
170	0.77	0.80	0.80	0.82	0.80	0.81	0.79	0.77	0.81	0.79	0.81	0.78						
175	0.78	0.81	0.80	0.82	0.81	0.82	0.79	0.79	0.82	0.80	0.83	0.80						
180	0.79	0.81	0.81	0.83	0.82	0.82	0.79	0.80	0.82	0.82	0.83	0.81						

C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-14


γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

I (cd)



1000 lm

$\kappa = 1$



F = 1000 lm
 K = 0.7
 Hcc = 0.8 m
 Hfc = 0.0 m
 Eave = 100 lx

	Pcc	Pw	Pfc
—————	70	50	30
—————	50	30	20

