


室内灯具光度数据

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

光源数据		光度数据				光效: 2.87 lm/W
型号	5050	峰值光强(cd)	10.86	S/MH(C0/180)	1.25	
标称功率(W)		灯具效率(%)	100.0	S/MH(C90/270)	1.25	
额定电源电压(V)	24	总光通量(lm)	32.952	η UP,DN(C0-180)	2.0,47.4	
额定光通量(lm)	32.9362	CIE分类	直接	η UP,DN(C180-360)	2.2,48.3	
灯具内光源数(只)	1	上射光通比(%)	4.3	CIBSE SHR NOM	1.25	
实测电源电压(V)		下射光通比(%)	95.8	CIBSE SHR MAX	1.35	



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

灯具环带光通量

环带光通量：

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ(°)	Φ环	Φ总	%lum, lamp
10	10.68	10.67	10.64	10.67	10.67	10.69	10.69	10.68	0- 10	1.028	1.028	3.12,3.12
20	10.07	10.06	10.05	10.08	10.08	10.11	10.10	10.09	10- 20	2.942	3.970	12,12.1
30	9.092	9.097	9.087	9.119	9.144	9.179	9.149	9.134	20- 30	4.445	8.415	25.5,25.6
40	7.817	7.830	7.796	7.846	7.906	7.940	7.900	7.878	30- 40	5.336	13.75	41.7,41.7
50	6.316	6.334	6.299	6.356	6.428	6.476	6.446	6.406	40- 50	5.514	19.26	58.5,58.5
60	4.700	4.718	4.697	4.723	4.797	4.877	4.844	4.803	50- 60	4.998	24.26	73.6,73.7
70	3.046	3.075	3.078	3.057	3.115	3.211	3.213	3.172	60- 70	3.908	28.17	85.5,85.5
80	1.471	1.499	1.511	1.460	1.499	1.595	1.632	1.602	70- 80	2.448	30.62	92.9,93
90	0.3096	0.2687	0.3100	0.2656	0.3285	0.3552	0.2691	0.3419	80- 90	0.9253	31.54	95.7,95.8
100	0.1934	0.1940	0.2063	0.1743	0.1602	0.2281	0.2654	0.2417	90-100	0.2514	31.79	96.5,96.5
110	0.1934	0.1937	0.2093	0.1803	0.1593	0.2252	0.2616	0.2319	100-110	0.2187	32.01	97.2,97.2
120	0.1934	0.1954	0.2222	0.1956	0.1794	0.2267	0.2597	0.2297	110-120	0.2083	32.22	97.8,97.8
130	0.1934	0.2050	0.2330	0.2141	0.1957	0.2313	0.2597	0.2306	120-130	0.1939	32.42	98.4,98.4
140	0.2024	0.2269	0.2483	0.2308	0.2141	0.2365	0.2597	0.2338	130-140	0.1748	32.59	98.9,99
150	0.2155	0.2454	0.2684	0.2457	0.2309	0.2435	0.2597	0.2410	140-150	0.1496	32.74	99.4,99.4
160	0.2366	0.2586	0.2684	0.2538	0.2454	0.2490	0.2597	0.2471	150-160	0.1149	32.85	99.7,99.8
170	0.2510	0.2602	0.2668	0.2593	0.2504	0.2586	0.2597	0.2543	160-170	0.0722	32.93	99.9,100
180	0.2568	0.2613	0.2655	0.2640	0.2540	0.2613	0.2626	0.2611	170-180	0.0247	32.95	100,100
单位:°	光强:cd									单位:lm		

锥面光通量(90度)：16.53 lm

%lum = 50.2%
%lamp = 50.2%


锥面光通量(130度)：26.381 lm

%lum = 80.1%
%lamp = 80.1%

C角度范围： 0度 - 360度 C角度间隔：30.0度 测试速度：快速 环境温度:25.3℃ 测试人员： 测试日期:2025-03-06	γ角度范围： 0度 - 180度 γ角度间隔： 1.0度 测试系统：远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注：
--	--

灯具亮度限制曲线

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



平均亮度值 cd/(m2)		
γ (°)	C0/180	C90/270
85	773	767
80	736	757
75	753	769
70	775	783
65	797	799
60	817	817
55	836	835
50	855	852
45	872	868


C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

工作面利用系数和灯具概算曲线

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: Olymبيا lighting	发光口面:	遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	工 作 面 利 用 系 数															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.03	1.03	1.03	.98	.98	.98	.96
1.0	1.02	.98	.94	.90	.96	.92	.95	.91	.88	.90	.87	.85	.86	.83	.81	.79
2.0	.89	.82	.76	.87	.80	.75	.82	.77	.72	.78	.74	.70	.75	.71	.68	.65
3.0	.78	.70	.63	.76	.68	.62	.72	.66	.60	.69	.63	.59	.66	.61	.57	.55
4.0	.69	.60	.53	.67	.59	.53	.64	.57	.51	.61	.55	.50	.59	.53	.49	.47
5.0	.61	.52	.46	.60	.52	.45	.57	.50	.44	.55	.49	.43	.53	.47	.43	.40
6.0	.55	.46	.40	.54	.46	.39	.52	.44	.39	.50	.43	.38	.48	.42	.37	.35
7.0	.50	.41	.35	.49	.41	.35	.47	.40	.34	.45	.39	.34	.44	.38	.33	.31
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.40	.34	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.38	.32	.27	.37	.31	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.35	.29	.25	.34	.29	.24	.23



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

墙面和天花板利用系数

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm					
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B			灯具类型:		灯具重量:
灯具规格:			外型尺寸: Length=1m		测试编号:
制造厂商: OLympia lighting			发光口面:		遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	墙 壁 面 利 用 系 数															
0.0																
1.0	.322	.183	.058	.313	.179	.057	.298	.171	.055	.283	.163	.052	.270	.156	.050	
2.0	.298	.163	.050	.290	.160	.049	.276	.154	.048	.263	.148	.046	.251	.142	.045	
3.0	.273	.146	.044	.267	.143	.043	.254	.138	.042	.243	.133	.041	.232	.128	.040	
4.0	.251	.131	.038	.245	.128	.038	.234	.124	.037	.224	.120	.036	.214	.116	.035	
5.0	.231	.118	.034	.226	.116	.034	.216	.113	.033	.207	.109	.032	.198	.106	.032	
6.0	.214	.107	.031	.209	.106	.030	.201	.103	.030	.192	.100	.029	.184	.097	.029	
7.0	.199	.098	.028	.195	.097	.028	.187	.094	.027	.179	.092	.027	.172	.089	.026	
8.0	.186	.091	.026	.182	.090	.025	.175	.087	.025	.168	.085	.025	.161	.083	.024	
9.0	.174	.084	.023	.170	.083	.023	.164	.081	.023	.158	.079	.023	.152	.077	.022	
10.0	.163	.078	.022	.160	.077	.022	.154	.076	.021	.148	.074	.021	.143	.072	.021	

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	天花板利用系数															
0.0	.223	.223	.223	.191	.191	.191	.130	.130	.130	.075	.075	.075	.024	.024	.024	
1.0	.214	.189	.166	.183	.162	.143	.125	.112	.099	.072	.065	.058	.023	.021	.019	
2.0	.206	.165	.130	.177	.142	.113	.121	.098	.079	.070	.057	.046	.022	.018	.015	
3.0	.198	.148	.107	.170	.127	.093	.117	.088	.065	.067	.052	.038	.022	.017	.013	
4.0	.191	.134	.091	.164	.116	.079	.113	.081	.056	.065	.047	.033	.021	.015	.011	
5.0	.183	.124	.081	.157	.107	.070	.108	.075	.049	.063	.044	.029	.020	.014	.010	
6.0	.176	.116	.073	.151	.100	.063	.104	.070	.045	.061	.041	.027	.020	.014	.009	
7.0	.169	.109	.067	.146	.095	.058	.101	.066	.041	.058	.039	.025	.019	.013	.008	
8.0	.163	.103	.062	.140	.090	.054	.097	.063	.039	.056	.037	.023	.018	.012	.008	
9.0	.157	.098	.059	.135	.085	.052	.094	.060	.037	.054	.035	.022	.018	.012	.007	
10.0	.151	.094	.056	.130	.082	.049	.090	.058	.035	.053	.034	.021	.017	.011	.007	

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度: 25.3℃ 测试人员: 测试日期: 2025-03-06	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度: 65.0% 测试距离: 6.360米 [K=1.0000] 备注:
--	---

UGR(Unified Glare Rating)数据表

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm											
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B					灯具类型:			灯具重量:			
灯具规格:					外型尺寸: Length=1m			测试编号:			
制造厂商: OLympia lighting					发光口面:			遮光角:			
反射比: 天花板		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
墙面		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
工作面		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
房间尺寸		横向(Viewed crosswise)					纵向(Viewed endwise)				
x = 2H y = 2H	2H	23.6	25.1	24.0	25.4	25.7	23.7	25.1	24.0	25.4	25.7
	3H	25.2	26.6	25.6	26.9	27.2	25.3	26.6	25.6	26.9	27.3
	4H	25.9	27.2	26.3	27.5	27.9	26.0	27.3	26.3	27.6	27.9
	6H	26.5	27.7	26.9	28.0	28.4	26.5	27.8	26.9	28.1	28.5
	8H	26.7	27.9	27.1	28.2	28.6	26.8	27.9	27.2	28.3	28.7
	12H	26.8	28.0	27.3	28.3	28.7	26.9	28.1	27.3	28.4	28.8
4H	2H	24.3	25.6	24.6	25.9	26.2	24.3	25.6	24.6	25.9	26.2
	3H	26.0	27.2	26.5	27.5	27.9	26.1	27.2	26.5	27.6	28.0
	4H	26.9	27.9	27.3	28.3	28.7	26.9	28.0	27.4	28.4	28.8
	6H	27.6	28.5	28.0	28.9	29.4	27.6	28.6	28.1	29.0	29.4
	8H	27.8	28.7	28.3	29.1	29.6	27.9	28.8	28.4	29.2	29.7
	12H	28.1	28.8	28.5	29.3	29.8	28.2	28.9	28.6	29.4	29.9
8H	4H	27.2	28.0	27.7	28.5	29.0	27.2	28.1	27.7	28.5	29.0
	6H	28.0	28.8	28.6	29.2	29.8	28.1	28.8	28.6	29.3	29.8
	8H	28.4	29.1	28.9	29.6	30.1	28.5	29.2	29.1	29.7	30.2
	12H	28.8	29.3	29.3	29.8	30.4	28.9	29.4	29.4	29.9	30.5
12H	4H	27.2	28.0	27.7	28.5	29.0	27.2	28.0	27.7	28.5	29.0
	6H	28.1	28.8	28.7	29.3	29.8	28.2	28.8	28.7	29.3	29.9
	8H	28.6	29.1	29.1	29.6	30.2	28.7	29.2	29.2	29.7	30.3
不同间隔布灯时,观察者位置引起的UGR变化(CIE Pub.117):											
S = 1.0H		+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H		+ 0.1 / - 0.3					+ 0.1 / - 0.3				

依据CIE Pub.117计算, 32.941m光源光通表格中的数据需要进行修正(81og(F/F0) = -11.9).
出光口面积: 0.0115 m2

C角度范围: 0度 - 360度	γ角度范围: 0度 - 180度
C角度间隔: 30.0度	γ角度间隔: 1.0度
测试速度: 快速	测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境温度:25.3℃	环境湿度:65.0%
测试人员:	测试距离:6.360米 [K=1.0000]
测试日期:2025-03-06	备注:

UF利用系数表

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:


反 射 比 / REFLECTANCE										
天花板	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
墙壁	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
室形指数	利用系数 UTILIZATION FACTORS(%) k(RI) x RCR = 5									
k = 0.60	56	44	37	55	44	37	54	43	37	30
0.80	66	54	46	64	53	46	62	52	46	38
1.00	74	63	55	73	62	55	70	63	54	46
1.25	81	70	63	79	69	62	76	67	61	53
1.50	86	76	68	84	75	68	81	72	66	58
2.00	93	84	77	91	82	76	87	80	74	66
2.50	97	89	82	95	87	81	90	84	79	70
3.00	100	93	87	98	91	86	93	88	83	74
4.00	104	98	93	102	96	92	97	92	88	78
5.00	107	102	97	104	99	96	99	95	92	81
ROOM INDEX	UF (总)									UF (直接)
依据标准文件 DIN EN 13032-2 2004			悬挂灯				安装距高比 SHR NOM = 1.25			

C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

灯 具 等 光 强 曲 线

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

灯 具 有 效 平 均 照 度 图

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

平面等照度曲线

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

LED筒灯平均亮度报告


实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

平均亮度	数值 (cd/m2)
L横 (65) av	805
L横 (75) av	761
L横 (85) av	789
L纵 (65) av	814
L纵 (75) av	789
L纵 (85) av	832
L45 (65) av	813
L45 (75) av	781
L45 (85) av	822

注:依据标准 GB/T 29293-2012 计算

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度:25.3℃ 测试人员: 测试日期:2025-03-06	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注:
--	---

平面照度曲线



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

光 强 分 布 数 据 表 格

实测参数: U:24.00V I:0.4788A P:11.49W PF:1.000 Freq:0Hz 实检光通: 32.9362x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:


表--1单位: cd

C (DEG) γ (DEG)	0	30	60	90	120	150	180	210	240	270	300	330						
0	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9	10.9						
5	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8						
10	10.7	10.7	10.7	10.6	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.7						
15	10.4	10.4	10.4	10.4	10.4	10.4	10.4	10.5	10.4	10.4	10.4	10.4						
20	10.1	10.1	10.1	10.0	10.1	10.1	10.1	10.1	10.1	10.1	10.1	10.1						
25	9.62	9.61	9.64	9.61	9.65	9.64	9.66	9.70	9.68	9.67	9.65	9.66						
30	9.09	9.09	9.11	9.09	9.12	9.12	9.14	9.19	9.17	9.15	9.13	9.14						
35	8.49	8.49	8.50	8.47	8.52	8.51	8.56	8.60	8.59	8.56	8.54	8.54						
40	7.82	7.82	7.84	7.80	7.84	7.85	7.91	7.95	7.93	7.90	7.89	7.87						
45	7.09	7.09	7.10	7.06	7.11	7.13	7.18	7.23	7.23	7.19	7.18	7.15						
50	6.32	6.33	6.34	6.30	6.35	6.37	6.43	6.48	6.47	6.45	6.43	6.38						
55	5.52	5.52	5.55	5.51	5.54	5.57	5.63	5.68	5.70	5.66	5.63	5.59						
60	4.70	4.70	4.73	4.70	4.71	4.73	4.80	4.86	4.89	4.84	4.83	4.78						
65	3.87	3.88	3.91	3.88	3.88	3.89	3.95	4.02	4.06	4.02	4.00	3.96						
70	3.05	3.05	3.10	3.08	3.06	3.05	3.11	3.17	3.25	3.21	3.20	3.15						
75	2.24	2.25	2.30	2.29	2.25	2.24	2.29	2.35	2.44	2.41	2.40	2.34						
80	1.47	1.48	1.52	1.51	1.47	1.45	1.50	1.55	1.64	1.63	1.64	1.57						
85	0.77	0.77	0.80	0.77	0.74	0.76	0.81	0.86	0.89	0.90	0.91	0.85						
90	0.31	0.28	0.26	0.31	0.24	0.29	0.33	0.37	0.34	0.27	0.33	0.35						
95	0.20	0.19	0.21	0.23	0.18	0.18	0.19	0.24	0.25	0.27	0.27	0.23						
100	0.19	0.19	0.20	0.21	0.17	0.17	0.16	0.21	0.25	0.27	0.27	0.22						
105	0.19	0.19	0.20	0.20	0.17	0.18	0.16	0.19	0.26	0.26	0.26	0.21						
110	0.19	0.19	0.20	0.21	0.18	0.18	0.16	0.19	0.26	0.26	0.26	0.20						
115	0.19	0.19	0.19	0.22	0.19	0.19	0.17	0.19	0.26	0.26	0.26	0.20						
120	0.19	0.20	0.19	0.22	0.19	0.20	0.18	0.19	0.26	0.26	0.26	0.20						
125	0.19	0.20	0.19	0.23	0.20	0.21	0.19	0.19	0.26	0.26	0.26	0.20						
130	0.19	0.21	0.20	0.23	0.21	0.22	0.20	0.20	0.26	0.26	0.26	0.20						
135	0.20	0.22	0.21	0.24	0.22	0.23	0.21	0.21	0.26	0.26	0.26	0.21						
140	0.20	0.23	0.22	0.25	0.23	0.23	0.21	0.21	0.26	0.26	0.26	0.21						
145	0.21	0.24	0.23	0.26	0.24	0.24	0.22	0.22	0.26	0.26	0.26	0.21						
150	0.22	0.25	0.24	0.27	0.24	0.25	0.23	0.22	0.26	0.26	0.26	0.22						
155	0.23	0.25	0.25	0.27	0.24	0.26	0.24	0.23	0.26	0.26	0.26	0.22						
160	0.24	0.26	0.26	0.27	0.25	0.26	0.25	0.23	0.26	0.26	0.26	0.23						
165	0.24	0.26	0.26	0.27	0.25	0.26	0.25	0.25	0.26	0.26	0.26	0.24						
170	0.25	0.26	0.26	0.27	0.26	0.26	0.25	0.25	0.27	0.26	0.26	0.25						
175	0.25	0.26	0.26	0.27	0.26	0.26	0.25	0.25	0.27	0.26	0.26	0.25						
180	0.26	0.26	0.26	0.27	0.26	0.27	0.25	0.26	0.27	0.26	0.26	0.26						

C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06


γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

I (cd)



1000 lm

$\kappa = 1$



F = 1000 lm
 K = 0.7
 Hcc = 0.8 m
 Hfc = 0.0 m
 Eave = 100 lx

	Pcc	Pw	Pfc
—————	70	50	30
—————	50	30	20

