


室内灯具光度数据

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

光源数据		光度数据				光效: 9.84 lm/W
型号	5050	峰值光强(cd)	18.87	S/MH(C0/180)	1.26	
标称功率(W)		灯具效率(%)	100.0	S/MH(C90/270)	1.25	
额定电源电压(V)	24	总光通量(lm)	55.946	η UP,DN(C0-180)	2.0,47.5	
额定光通量(lm)	55.9462	CIE分类	直接	η UP,DN(C180-360)	2.2,48.3	
灯具内光源数(只)	1	上射光通比(%)	4.2	CIBSE SHR NOM	1.25	
实测电源电压(V)		下射光通比(%)	95.8	CIBSE SHR MAX	1.35	



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

灯具环带光通量

环带光通量：

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ(°)	Φ环	Φ总	%lum, lamp
10	18.42	18.47	18.50	18.59	18.61	18.60	18.53	18.47	0- 10	1.785	1.785	3.19,3.19
20	17.26	17.36	17.46	17.60	17.62	17.61	17.50	17.37	10- 20	5.103	6.888	12.3,12.3
30	15.47	15.62	15.79	15.95	15.96	15.98	15.84	15.65	20- 30	7.698	14.59	26.1,26.1
40	13.18	13.37	13.59	13.75	13.72	13.80	13.67	13.42	30- 40	9.218	23.80	42.5,42.5
50	10.53	10.75	11.02	11.13	11.06	11.21	11.13	10.82	40- 50	9.490	33.29	59.5,59.5
60	7.646	7.908	8.228	8.241	8.135	8.326	8.348	7.992	50- 60	8.541	41.84	74.8,74.8
70	4.692	4.999	5.357	5.258	5.121	5.353	5.495	5.093	60- 70	6.571	48.41	86.5,86.5
80	1.888	2.218	2.591	2.401	2.245	2.509	2.743	2.312	70- 80	3.953	52.36	93.6,93.6
90	0.2162	0.2643	0.3205	0.2730	0.2104	0.3349	0.4343	0.3321	80- 90	1.264	53.62	95.8,95.8
100	0.2277	0.2699	0.3408	0.2902	0.2364	0.3478	0.4303	0.3422	90-100	0.3293	53.95	96.4,96.4
110	0.2737	0.3002	0.3639	0.3248	0.2681	0.3766	0.4534	0.3797	100-110	0.3469	54.30	97.1,97.1
120	0.3112	0.3420	0.3870	0.3580	0.3026	0.3954	0.4563	0.3883	110-120	0.3524	54.65	97.7,97.7
130	0.3487	0.3796	0.4130	0.3826	0.3373	0.4070	0.4592	0.4028	120-130	0.3416	54.99	98.3,98.3
140	0.3775	0.4041	0.4332	0.4100	0.3661	0.4228	0.4592	0.4086	130-140	0.3105	55.30	98.9,98.9
150	0.4035	0.4258	0.4534	0.4331	0.4036	0.4358	0.4592	0.4230	140-150	0.2641	55.57	99.3,99.3
160	0.4352	0.4488	0.4765	0.4576	0.4381	0.4546	0.4678	0.4461	150-160	0.2039	55.77	99.7,99.7
170	0.4553	0.4676	0.4794	0.4721	0.4612	0.4647	0.4649	0.4649	160-170	0.1301	55.90	99.9,99.9
180	0.4640	0.4733	0.4794	0.4764	0.4640	0.4748	0.4794	0.4764	170-180	0.0448	55.95	100,100
单位:°	光强:cd									单位:lm		

锥面光通量(90度)：28.594 lm

%lum = 51.1%
%lamp = 51.1%


锥面光通量(130度)：45.418 lm

%lum = 81.2%
%lamp = 81.2%

C角度范围： 0度 - 360度 C角度间隔： 30.0度 测试速度：快速 环境温度:25.3℃ 测试人员： 测试日期:2025-03-06	γ角度范围： 0度 - 180度 γ角度间隔： 1.0度 测试系统：远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注：
---	--

灯具亮度限制曲线

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



平均亮度值 cd/(m2)		
γ (°)	C0/180	C90/270
85	731	1337
80	947	1297
75	1095	1326
70	1195	1361
65	1271	1396
60	1332	1430
55	1382	1461
50	1427	1490
45	1464	1517


C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

工作面利用系数和灯具概算曲线

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	工 作 面 利 用 系 数															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.03	1.03	1.03	.98	.98	.98	.96
1.0	1.03	.98	.94	.90	.96	.92	.95	.92	.89	.90	.88	.85	.86	.84	.82	.80
2.0	.89	.82	.77	.87	.81	.75	.83	.78	.73	.79	.75	.71	.75	.72	.69	.66
3.0	.78	.70	.64	.76	.69	.63	.73	.66	.61	.70	.64	.60	.66	.62	.58	.56
4.0	.69	.61	.54	.68	.60	.53	.65	.58	.52	.62	.56	.51	.59	.54	.50	.47
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.49	.44	.53	.48	.43	.41
6.0	.56	.47	.40	.55	.46	.40	.52	.45	.39	.50	.44	.39	.48	.43	.38	.36
7.0	.51	.42	.36	.49	.41	.35	.48	.40	.35	.46	.39	.34	.44	.38	.34	.32
8.0	.46	.38	.32	.45	.37	.31	.44	.36	.31	.42	.35	.31	.40	.35	.30	.28
9.0	.42	.34	.29	.42	.34	.28	.40	.33	.28	.39	.32	.28	.37	.32	.27	.25
10.0	.39	.31	.26	.38	.31	.26	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

墙面和天花板利用系数

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm					
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R			灯具类型:		灯具重量:
灯具规格:			外型尺寸: Length=1m		测试编号:
制造厂商: OLympia lighting			发光口面:		遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	墙 壁 面 利 用 系 数															
0.0																
1.0	.314	.178	.056	.305	.174	.055	.290	.166	.053	.275	.159	.051	.262	.152	.049	
2.0	.293	.160	.049	.285	.157	.048	.271	.151	.047	.259	.145	.045	.247	.140	.044	
3.0	.270	.144	.043	.263	.141	.042	.251	.136	.041	.239	.131	.040	.229	.127	.039	
4.0	.249	.129	.038	.243	.127	.038	.232	.123	.037	.221	.119	.036	.212	.115	.035	
5.0	.230	.117	.034	.224	.115	.034	.214	.112	.033	.205	.108	.032	.197	.105	.032	
6.0	.213	.107	.031	.208	.105	.030	.199	.102	.030	.191	.099	.029	.183	.096	.029	
7.0	.198	.098	.028	.194	.096	.027	.186	.094	.027	.178	.091	.027	.171	.089	.026	
8.0	.185	.090	.025	.181	.089	.025	.174	.087	.025	.167	.085	.024	.160	.082	.024	
9.0	.173	.084	.023	.170	.083	.023	.163	.081	.023	.157	.079	.023	.151	.077	.022	
10.0	.163	.078	.022	.160	.077	.021	.154	.075	.021	.148	.073	.021	.143	.072	.021	

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	天花板利用系数															
0.0	.222	.222	.222	.190	.190	.190	.130	.130	.130	.074	.074	.074	.024	.024	.024	
1.0	.212	.188	.166	.182	.161	.143	.124	.111	.099	.072	.064	.057	.023	.021	.019	
2.0	.204	.164	.130	.175	.141	.112	.120	.098	.078	.069	.057	.046	.022	.018	.015	
3.0	.197	.147	.107	.169	.126	.092	.116	.088	.065	.067	.051	.038	.021	.017	.013	
4.0	.189	.133	.091	.162	.115	.079	.112	.080	.056	.065	.047	.033	.021	.015	.011	
5.0	.182	.123	.080	.156	.107	.069	.108	.074	.049	.062	.044	.029	.020	.014	.010	
6.0	.175	.115	.072	.150	.099	.063	.104	.070	.044	.060	.041	.026	.019	.013	.009	
7.0	.168	.108	.066	.144	.094	.058	.100	.066	.041	.058	.039	.024	.019	.013	.008	
8.0	.161	.102	.062	.139	.089	.054	.096	.062	.038	.056	.037	.023	.018	.012	.008	
9.0	.155	.097	.058	.134	.084	.051	.093	.059	.036	.054	.035	.021	.017	.012	.007	
10.0	.150	.093	.055	.129	.081	.048	.089	.057	.034	.052	.034	.021	.017	.011	.007	

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度: 25.3℃ 测试人员: 测试日期: 2025-03-06	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度: 65.0% 测试距离: 6.360米 [K=1.0000] 备注:
--	---

UGR(Unified Glare Rating)数据表

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm												
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R					灯具类型:			灯具重量:				
灯具规格:					外型尺寸: Length=1m			测试编号:				
制造厂商: OLympia lighting					发光口面:			遮光角:				
反射比:		天花板	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
		墙面	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
		工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
房间尺寸			横向(Viewed crosswise)					纵向(Viewed endwise)				
x = 2H y = 2H	2H	23.5	25.0	23.8	25.2	25.5	23.7	25.2	24.1	25.5	25.8	
	3H	24.9	26.3	25.3	26.6	26.9	25.4	26.7	25.7	27.0	27.3	
	4H	25.5	26.8	25.9	27.1	27.5	26.0	27.3	26.4	27.7	28.0	
	6H	25.9	27.1	26.3	27.4	27.8	26.6	27.8	27.0	28.2	28.5	
	8H	26.0	27.2	26.4	27.5	27.9	26.8	28.0	27.2	28.3	28.7	
	12H	26.0	27.2	26.5	27.5	27.9	27.0	28.1	27.4	28.5	28.9	
4H	2H	24.1	25.4	24.5	25.7	26.1	24.3	25.6	24.7	25.9	26.3	
	3H	25.7	26.9	26.2	27.2	27.6	26.1	27.2	26.5	27.6	28.0	
	4H	26.4	27.5	26.9	27.9	28.3	26.9	28.0	27.4	28.3	28.8	
	6H	26.9	27.9	27.4	28.3	28.7	27.6	28.5	28.1	29.0	29.4	
	8H	27.1	27.9	27.6	28.4	28.9	27.9	28.7	28.4	29.2	29.7	
	12H	27.2	28.0	27.7	28.4	28.9	28.1	28.9	28.6	29.4	29.8	
8H	4H	26.7	27.6	27.2	28.0	28.5	27.2	28.0	27.6	28.5	28.9	
	6H	27.4	28.1	27.9	28.6	29.1	28.0	28.7	28.5	29.2	29.7	
	8H	27.6	28.2	28.1	28.7	29.3	28.4	29.0	28.9	29.5	30.1	
	12H	27.8	28.3	28.3	28.8	29.4	28.7	29.3	29.3	29.8	30.3	
12H	4H	26.8	27.5	27.3	28.0	28.5	27.2	27.9	27.7	28.4	28.9	
	6H	27.5	28.1	28.0	28.6	29.1	28.1	28.7	28.6	29.2	29.7	
	8H	27.7	28.3	28.3	28.8	29.4	28.5	29.0	29.0	29.5	30.1	
不同间隔布灯时,观察者位置引起的UGR变化(CIE Pub.117):												
S = 1.0H		+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H		+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H		+ 0.2 / - 0.3					+ 0.1 / - 0.2					

依据CIE Pub.117计算, 55.951lm光源光通表格中的数据需要进行修正(81log(F/F0) = -10.0).
出光口面积: 0.0115 m2

C角度范围: 0度 - 360度	γ角度范围: 0度 - 180度
C角度间隔: 30.0度	γ角度间隔: 1.0度
测试速度: 快速	测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境温度:25.3℃	环境湿度:65.0%
测试人员:	测试距离:6.360米 [K=1.0000]
测试日期:2025-03-06	备注:

UF利用系数表

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:


反 射 比 / REFLECTANCE										
天花板	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
墙壁	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
室形指数	利用系数 UTILIZATION FACTORS(%) k(RI) x RCR = 5									
k = 0.60	56	45	38	55	44	38	54	44	37	31
0.80	66	54	47	65	54	47	63	53	46	39
1.00	74	63	56	73	62	55	70	64	55	47
1.25	81	71	64	80	70	63	77	68	62	54
1.50	86	76	69	85	75	69	81	73	67	59
2.00	93	85	78	91	83	77	87	80	75	66
2.50	97	89	83	95	88	82	91	85	80	70
3.00	101	94	88	98	92	87	94	88	84	74
4.00	105	99	94	102	97	92	97	93	89	79
5.00	107	102	98	104	100	96	99	96	92	82
ROOM INDEX	UF (总)									UF (直接)
依据标准文件 DIN EN 13032-2 2004			悬挂灯				安装距高比 SHR NOM = 1.25			

C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

灯 具 等 光 强 曲 线

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

灯 具 有 效 平 均 照 度 图

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

平面等照度曲线

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

LED筒灯平均亮度报告


实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

平均亮度	数值 (cd/m2)
L横 (65) av	1317
L横 (75) av	1160
L横 (85) av	842
L纵 (65) av	1410
L纵 (75) av	1350
L纵 (85) av	1399
L45 (65) av	1368
L45 (75) av	1257
L45 (85) av	1073

注:依据标准 GB/T 29293-2012 计算

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度:25.3℃ 测试人员: 测试日期:2025-03-06	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注:
--	---

平面照度曲线



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

光 强 分 布 数 据 表 格

实测参数: U:24.00V I:0.2369A P:5.686W PF:1.000 Freq:0Hz 实检光通: 55.9462x1 lm																	
灯具名称: SF15-24V-5050-70-SPI-RGBW(4000K)-R									灯具类型:						灯具重量:		
灯具规格:									外型尺寸: Length=1m						测试编号:		
制造厂商: OLympia lighting									发光口面:						遮光角:		


表--1单位: cd

C (DEG) γ (DEG)	0	30	60	90	120	150	180	210	240	270	300	330						
0	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9	18.9						
5	18.7	18.7	18.8	18.8	18.8	18.8	18.8	18.8	18.8	18.8	18.8	18.8						
10	18.4	18.4	18.5	18.5	18.6	18.6	18.6	18.6	18.6	18.5	18.5	18.5						
15	17.9	18.0	18.0	18.1	18.2	18.2	18.2	18.2	18.2	18.1	18.0	18.0						
20	17.3	17.3	17.4	17.5	17.6	17.6	17.6	17.6	17.6	17.5	17.4	17.3						
25	16.4	16.5	16.6	16.7	16.8	16.9	16.9	16.9	16.9	16.7	16.6	16.5						
30	15.5	15.6	15.7	15.8	15.9	16.0	16.0	16.0	16.0	15.8	15.7	15.6						
35	14.4	14.5	14.6	14.7	14.9	14.9	14.9	15.0	15.0	14.8	14.7	14.5						
40	13.2	13.3	13.4	13.6	13.7	13.8	13.7	13.8	13.8	13.7	13.5	13.3						
45	11.9	12.0	12.2	12.3	12.5	12.5	12.4	12.5	12.6	12.4	12.3	12.0						
50	10.5	10.7	10.8	11.0	11.2	11.1	11.1	11.2	11.2	11.1	11.0	10.7						
55	9.10	9.24	9.46	9.64	9.76	9.67	9.62	9.72	9.86	9.77	9.58	9.28						
60	7.65	7.78	8.04	8.23	8.31	8.18	8.14	8.23	8.42	8.35	8.15	7.83						
65	6.17	6.31	6.59	6.79	6.83	6.67	6.63	6.73	6.95	6.92	6.72	6.37						
70	4.69	4.85	5.15	5.36	5.35	5.17	5.12	5.22	5.48	5.49	5.27	4.91						
75	3.25	3.43	3.73	3.95	3.89	3.71	3.65	3.77	4.04	4.09	3.86	3.50						
80	1.89	2.07	2.37	2.59	2.50	2.30	2.25	2.37	2.65	2.74	2.49	2.13						
85	0.73	0.84	1.09	1.34	1.20	1.02	0.96	1.07	1.33	1.46	1.21	0.89						
90	0.22	0.24	0.29	0.32	0.30	0.25	0.21	0.28	0.39	0.43	0.38	0.28						
95	0.22	0.25	0.28	0.32	0.29	0.26	0.22	0.27	0.41	0.42	0.39	0.27						
100	0.23	0.26	0.28	0.34	0.30	0.28	0.24	0.27	0.42	0.43	0.41	0.28						
105	0.25	0.27	0.29	0.35	0.31	0.30	0.25	0.29	0.44	0.44	0.42	0.29						
110	0.27	0.29	0.31	0.36	0.34	0.31	0.27	0.31	0.45	0.45	0.43	0.33						
115	0.29	0.32	0.33	0.38	0.35	0.33	0.28	0.33	0.45	0.45	0.43	0.33						
120	0.31	0.34	0.34	0.39	0.36	0.35	0.30	0.34	0.45	0.46	0.43	0.35						
125	0.33	0.36	0.37	0.40	0.38	0.36	0.32	0.35	0.45	0.46	0.43	0.36						
130	0.35	0.38	0.38	0.41	0.39	0.38	0.34	0.36	0.46	0.46	0.44	0.37						
135	0.37	0.40	0.39	0.42	0.40	0.40	0.35	0.37	0.46	0.46	0.44	0.37						
140	0.38	0.40	0.40	0.43	0.41	0.41	0.37	0.39	0.46	0.46	0.44	0.37						
145	0.39	0.42	0.41	0.44	0.42	0.42	0.38	0.40	0.46	0.46	0.45	0.39						
150	0.40	0.43	0.42	0.45	0.43	0.44	0.40	0.40	0.47	0.46	0.45	0.40						
155	0.42	0.44	0.43	0.46	0.45	0.45	0.42	0.42	0.47	0.46	0.47	0.41						
160	0.44	0.46	0.44	0.48	0.45	0.46	0.44	0.43	0.48	0.47	0.47	0.42						
165	0.45	0.47	0.46	0.48	0.46	0.47	0.45	0.44	0.48	0.46	0.48	0.43						
170	0.46	0.47	0.46	0.48	0.47	0.48	0.46	0.45	0.48	0.46	0.48	0.45						
175	0.46	0.47	0.47	0.48	0.48	0.48	0.47	0.46	0.48	0.47	0.48	0.46						
180	0.46	0.47	0.47	0.48	0.48	0.48	0.46	0.47	0.48	0.48	0.48	0.47						

C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06


γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

I (cd)



1000 lm

$\kappa = 1$



F = 1000 lm
 K = 0.7
 Hcc = 0.8 m
 Hfc = 0.0 m
 Eave = 100 lx

	Pcc	Pw	Pfc
—————	70	50	30
—————	50	30	20

