


室内灯具光度数据

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

光源数据		光度数据				光效: 5.23 lm/W
型号	5050	峰值光强(cd)	19.44	S/MH(C0/180)	1.25	
标称功率(W)		灯具效率(%)	100.0	S/MH(C90/270)	1.25	
额定电源电压(V)	24	总光通量(lm)	59.107	η UP,DN(C0-180)	2.1,47.3	
额定光通量(lm)	59.1065	CIE分类	直接	η UP,DN(C180-360)	2.3,48.3	
灯具内光源数(只)	1	上射光通比(%)	4.4	CIBSE SHR NOM	1.25	
实测电源电压(V)		下射光通比(%)	95.6	CIBSE SHR MAX	1.35	



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

灯具环带光通量

环带光通量：

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ(°)	Φ环	Φ总	%lum, lamp
10	19.09	19.09	19.06	19.09	19.12	19.14	19.12	19.11	0- 10	1.840	1.840	3.11,3.11
20	17.99	18.01	17.99	18.03	18.08	18.11	18.07	18.06	10- 20	5.265	7.106	12,12
30	16.25	16.29	16.26	16.31	16.38	16.44	16.37	16.35	20- 30	7.956	15.06	25.5,25.5
40	13.97	14.02	13.97	14.05	14.16	14.23	14.14	14.11	30- 40	9.552	24.61	41.6,41.6
50	11.28	11.36	11.30	11.39	11.52	11.62	11.53	11.47	40- 50	9.877	34.49	58.4,58.4
60	8.394	8.465	8.432	8.479	8.599	8.756	8.686	8.615	50- 60	8.961	43.45	73.5,73.5
70	5.443	5.518	5.500	5.486	5.556	5.752	5.754	5.689	60- 70	7.007	50.46	85.4,85.4
80	2.623	2.700	2.687	2.628	2.700	2.853	2.926	2.881	70- 80	4.386	54.84	92.8,92.8
90	0.5527	0.4853	0.3242	0.4926	0.6163	0.6693	0.4991	0.6115	80- 90	1.657	56.50	95.6,95.6
100	0.3629	0.3454	0.3445	0.3137	0.2885	0.4289	0.4747	0.4227	90-100	0.4498	56.95	96.4,96.4
110	0.3486	0.3411	0.3821	0.3413	0.2972	0.4245	0.4862	0.4183	100-110	0.3969	57.35	97,97
120	0.3400	0.3554	0.4052	0.3791	0.3286	0.4346	0.4921	0.4212	110-120	0.3842	57.73	97.7,97.7
130	0.3657	0.3885	0.4284	0.4125	0.3629	0.4447	0.4921	0.4285	120-130	0.3629	58.10	98.3,98.3
140	0.3828	0.4231	0.4545	0.4401	0.3972	0.4519	0.4921	0.4372	130-140	0.3292	58.43	98.8,98.8
150	0.4199	0.4533	0.4921	0.4662	0.4314	0.4677	0.4921	0.4488	140-150	0.2807	58.71	99.3,99.3
160	0.4513	0.4821	0.5007	0.4837	0.4629	0.4763	0.4950	0.4677	150-160	0.2166	58.92	99.7,99.7
170	0.4743	0.4951	0.5007	0.4953	0.4857	0.4893	0.4950	0.4880	160-170	0.1372	59.06	99.9,99.9
180	0.4828	0.4994	0.5007	0.4967	0.4857	0.4951	0.5007	0.4982	170-180	0.0470	59.11	100,100
单位:°	光强:cd									单位:lm		

锥面光通量(90度)：29.592 lm


%lum = 50.1%
%lamp = 50.1%

锥面光通量(130度)：47.252 lm

%lum = 79.9%
%lamp = 79.9%

灯具亮度限制曲线

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



平均亮度值 cd/(m2)		
γ (°)	C0/180	C90/270
85	1391	1339
80	1327	1342
75	1361	1365
70	1398	1394
65	1437	1427
60	1475	1462
55	1510	1493
50	1542	1524
45	1573	1554


C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

工作面利用系数和灯具概算曲线

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	工 作 面 利 用 系 数															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.03	1.03	1.03	.98	.98	.98	.96
1.0	1.02	.98	.94	.99	.95	.92	.94	.91	.88	.90	.87	.85	.85	.83	.81	.79
2.0	.89	.82	.76	.86	.80	.75	.82	.77	.72	.78	.74	.70	.75	.71	.68	.65
3.0	.78	.69	.63	.76	.68	.62	.72	.66	.60	.69	.63	.59	.66	.61	.57	.55
4.0	.69	.60	.53	.67	.59	.52	.64	.57	.51	.61	.55	.50	.59	.53	.49	.47
5.0	.61	.52	.46	.60	.52	.45	.57	.50	.44	.55	.48	.43	.53	.47	.42	.40
6.0	.55	.46	.40	.54	.46	.39	.52	.44	.39	.50	.43	.38	.48	.42	.37	.35
7.0	.50	.41	.35	.49	.41	.35	.47	.40	.34	.45	.39	.34	.44	.38	.33	.31
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.41	.35	.30	.40	.34	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.32	.27	.38	.32	.27	.37	.31	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.35	.29	.25	.34	.28	.24	.22



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

墙面和天花板利用系数

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm					
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R			灯具类型:		灯具重量:
灯具规格:			外型尺寸: Length=1m		测试编号:
制造厂商: OLympia lighting			发光口面:		遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	墙 壁 面 利 用 系 数															
0.0																
1.0	.322	.183	.058	.313	.179	.057	.297	.171	.054	.283	.163	.052	.269	.156	.050	
2.0	.298	.163	.050	.290	.160	.049	.276	.153	.048	.263	.148	.046	.251	.142	.045	
3.0	.273	.145	.044	.267	.143	.043	.254	.138	.042	.242	.133	.041	.232	.128	.040	
4.0	.251	.130	.038	.245	.128	.038	.234	.124	.037	.223	.120	.036	.214	.116	.035	
5.0	.231	.118	.034	.226	.116	.034	.216	.112	.033	.207	.109	.032	.198	.106	.032	
6.0	.214	.107	.031	.209	.106	.030	.200	.103	.030	.192	.100	.029	.184	.097	.029	
7.0	.199	.098	.028	.195	.097	.028	.187	.094	.027	.179	.092	.027	.172	.089	.026	
8.0	.186	.091	.026	.182	.089	.025	.174	.087	.025	.167	.085	.024	.161	.083	.024	
9.0	.174	.084	.023	.170	.083	.023	.164	.081	.023	.157	.079	.023	.151	.077	.022	
10.0	.163	.078	.022	.160	.077	.022	.154	.075	.021	.148	.074	.021	.143	.072	.021	

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	天花板利用系数															
0.0	.224	.224	.224	.191	.191	.191	.131	.131	.131	.075	.075	.075	.024	.024	.024	
1.0	.215	.190	.167	.184	.163	.144	.126	.112	.100	.072	.065	.058	.023	.021	.019	
2.0	.207	.166	.131	.177	.143	.114	.122	.099	.079	.070	.057	.046	.022	.019	.015	
3.0	.199	.149	.108	.171	.128	.094	.117	.089	.066	.068	.052	.039	.022	.017	.013	
4.0	.192	.135	.092	.165	.117	.080	.113	.082	.057	.065	.048	.033	.021	.016	.011	
5.0	.184	.125	.082	.158	.108	.071	.109	.076	.050	.063	.044	.030	.020	.014	.010	
6.0	.177	.117	.074	.152	.101	.064	.105	.071	.045	.061	.042	.027	.020	.014	.009	
7.0	.170	.110	.068	.146	.095	.059	.101	.067	.042	.059	.039	.025	.019	.013	.008	
8.0	.164	.104	.063	.141	.090	.055	.098	.064	.039	.057	.037	.023	.018	.012	.008	
9.0	.158	.099	.060	.136	.086	.052	.094	.061	.037	.055	.036	.022	.018	.012	.007	
10.0	.152	.095	.057	.131	.083	.050	.091	.058	.036	.053	.034	.021	.017	.011	.007	

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度: 25.3℃ 测试人员: 测试日期: 2025-03-06	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度: 65.0% 测试距离: 6.360米 [K=1.0000] 备注:
--	---

UGR(Unified Glare Rating)数据表

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm											
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R						灯具类型:			灯具重量:		
灯具规格:						外型尺寸: Length=1m			测试编号:		
制造厂商: OLympia lighting						发光口面:			遮光角:		
反射比: 天花板		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
墙面		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
工作面		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
房间尺寸		横向(Viewed crosswise)					纵向(Viewed endwise)				
x = 2H y = 2H	2H	23.7	25.1	24.0	25.4	25.7	23.6	25.1	24.0	25.4	25.7
	3H	25.3	26.6	25.6	26.9	27.3	25.2	26.6	25.6	26.9	27.2
	4H	26.0	27.2	26.3	27.6	27.9	25.9	27.2	26.3	27.6	27.9
	6H	26.5	27.7	26.9	28.1	28.4	26.5	27.7	26.9	28.1	28.4
	8H	26.7	27.9	27.1	28.3	28.6	26.7	27.9	27.1	28.3	28.6
	12H	26.9	28.0	27.3	28.4	28.8	26.9	28.0	27.3	28.4	28.8
4H	2H	24.3	25.6	24.7	25.9	26.3	24.3	25.6	24.6	25.9	26.2
	3H	26.1	27.2	26.5	27.6	28.0	26.1	27.2	26.5	27.6	28.0
	4H	26.9	27.9	27.3	28.3	28.8	26.9	27.9	27.3	28.3	28.8
	6H	27.6	28.5	28.1	28.9	29.4	27.6	28.5	28.1	29.0	29.4
	8H	27.9	28.7	28.4	29.2	29.7	27.9	28.7	28.4	29.2	29.7
	12H	28.1	28.9	28.6	29.3	29.8	28.1	28.9	28.6	29.4	29.9
8H	4H	27.2	28.1	27.7	28.5	29.0	27.2	28.1	27.7	28.5	29.0
	6H	28.1	28.8	28.6	29.3	29.8	28.1	28.8	28.6	29.3	29.8
	8H	28.5	29.1	29.0	29.6	30.2	28.5	29.1	29.0	29.6	30.2
	12H	28.8	29.4	29.3	29.9	30.4	28.8	29.4	29.4	29.9	30.5
12H	4H	27.2	28.0	27.7	28.5	29.0	27.2	28.0	27.7	28.5	29.0
	6H	28.2	28.8	28.7	29.3	29.9	28.2	28.8	28.7	29.3	29.9
	8H	28.6	29.2	29.2	29.7	30.3	28.6	29.2	29.2	29.7	30.3
不同间隔布灯时,观察者位置引起的UGR变化(CIE Pub.117):											
S = 1.0H		+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H		+ 0.1 / - 0.3					+ 0.1 / - 0.3				

依据CIE Pub.117计算, 59.11lm光源光通表格中的数据需要进行修正(81log(F/F0) = -9.8).
出光口面积: 0.0115 m2

C角度范围: 0度 - 360度	γ角度范围: 0度 - 180度
C角度间隔: 30.0度	γ角度间隔: 1.0度
测试速度: 快速	测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境温度:25.3℃	环境湿度:65.0%
测试人员:	测试距离:6.360米 [K=1.0000]
测试日期:2025-03-06	备注:

UF利用系数表

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:


反 射 比 / REFLECTANCE										
天花板	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
墙壁	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
室形指数	利用系数 UTILIZATION FACTORS(%) k(RI) x RCR = 5									
k = 0.60	56	44	37	55	44	37	53	43	37	30
0.80	66	54	46	64	53	46	62	52	46	38
1.00	74	62	55	72	62	55	70	63	54	46
1.25	81	70	63	79	69	62	76	67	61	53
1.50	86	76	68	84	75	68	80	72	66	58
2.00	93	84	77	91	82	76	87	80	74	65
2.50	97	89	82	94	87	81	90	84	79	69
3.00	100	93	87	98	91	86	93	88	83	73
4.00	104	98	93	102	96	92	97	92	88	78
5.00	107	102	97	104	99	95	99	95	92	81
ROOM INDEX	UF (总)									UF (直接)
依据标准文件 DIN EN 13032-2 2004			悬挂灯				安装距高比 SHR _{NOM} = 1.25			

C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

灯 具 等 光 强 曲 线

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

灯 具 有 效 平 均 照 度 图

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度:25.3℃
测试人员:
测试日期:2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注:

平面等照度曲线

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

LED筒灯平均亮度报告


实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm		
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

平均亮度	数值 (cd/m2)
L横 (65) av	1440
L横 (75) av	1361
L横 (85) av	1420
L纵 (65) av	1459
L纵 (75) av	1410
L纵 (85) av	1476
L45 (65) av	1460
L45 (75) av	1399
L45 (85) av	1472

注:依据标准 GB/T 29293-2012 计算

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度:25.3℃ 测试人员: 测试日期:2025-03-06	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注:
--	---

平面照度曲线



C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

光 强 分 布 数 据 表 格

实测参数: U:24.00V I:0.4710A P:11.30W PF:1.000 Freq:0Hz 实检光通: 59.1065x1 lm																	
灯具名称: SF15-24V-5050-70-SPI-RGBW(2700K)-R									灯具类型:						灯具重量:		
灯具规格:									外型尺寸: Length=1m						测试编号:		
制造厂商: OLympia lighting									发光口面:						遮光角:		


表--1单位: cd

C (DEG) γ (DEG)	0	30	60	90	120	150	180	210	240	270	300	330						
0	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4						
5	19.4	19.3	19.4	19.3	19.4	19.4	19.4	19.4	19.4	19.4	19.4	19.4						
10	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1	19.1						
15	18.6	18.6	18.6	18.6	18.6	18.7	18.7	18.7	18.7	18.7	18.7	18.7						
20	18.0	18.0	18.0	18.0	18.0	18.0	18.1	18.1	18.1	18.1	18.1	18.1						
25	17.2	17.2	17.2	17.2	17.2	17.3	17.3	17.3	17.3	17.3	17.3	17.3						
30	16.3	16.3	16.3	16.3	16.3	16.3	16.4	16.4	16.4	16.4	16.4	16.3						
35	15.2	15.2	15.2	15.2	15.2	15.3	15.3	15.4	15.4	15.3	15.3	15.3						
40	14.0	14.0	14.0	14.0	14.0	14.1	14.2	14.2	14.2	14.1	14.1	14.1						
45	12.7	12.7	12.7	12.7	12.7	12.8	12.9	12.9	13.0	12.9	12.9	12.8						
50	11.3	11.4	11.4	11.3	11.4	11.4	11.5	11.6	11.7	11.5	11.5	11.4						
55	9.86	9.91	9.93	9.88	9.92	9.99	10.1	10.2	10.3	10.1	10.1	10.00						
60	8.39	8.45	8.48	8.43	8.45	8.51	8.60	8.70	8.81	8.69	8.68	8.55						
65	6.91	6.97	7.00	6.96	6.96	6.99	7.08	7.18	7.34	7.22	7.21	7.08						
70	5.44	5.50	5.54	5.50	5.48	5.49	5.56	5.64	5.86	5.75	5.75	5.62						
75	4.01	4.06	4.10	4.07	4.03	4.03	4.09	4.15	4.38	4.32	4.33	4.19						
80	2.62	2.68	2.72	2.69	2.63	2.63	2.70	2.78	2.93	2.93	2.95	2.81						
85	1.38	1.40	1.41	1.35	1.30	1.38	1.47	1.53	1.61	1.61	1.63	1.52						
90	0.55	0.52	0.45	0.32	0.44	0.55	0.62	0.69	0.65	0.50	0.61	0.62						
95	0.38	0.36	0.36	0.34	0.33	0.35	0.36	0.44	0.48	0.47	0.46	0.41						
100	0.36	0.35	0.34	0.34	0.31	0.31	0.29	0.38	0.48	0.47	0.45	0.39						
105	0.35	0.34	0.34	0.37	0.32	0.32	0.28	0.36	0.49	0.48	0.46	0.39						
110	0.35	0.34	0.34	0.38	0.35	0.33	0.30	0.36	0.49	0.49	0.46	0.38						
115	0.34	0.35	0.34	0.39	0.37	0.36	0.31	0.37	0.50	0.49	0.47	0.37						
120	0.34	0.36	0.35	0.41	0.38	0.38	0.33	0.37	0.50	0.49	0.47	0.37						
125	0.35	0.37	0.37	0.42	0.40	0.39	0.35	0.38	0.50	0.49	0.47	0.38						
130	0.37	0.39	0.39	0.43	0.42	0.41	0.36	0.39	0.50	0.49	0.47	0.38						
135	0.38	0.40	0.41	0.44	0.42	0.42	0.38	0.40	0.50	0.49	0.48	0.39						
140	0.38	0.42	0.42	0.45	0.44	0.44	0.40	0.41	0.50	0.49	0.48	0.40						
145	0.40	0.44	0.44	0.47	0.46	0.45	0.41	0.42	0.50	0.49	0.48	0.41						
150	0.42	0.45	0.46	0.49	0.47	0.47	0.43	0.44	0.50	0.49	0.48	0.42						
155	0.43	0.47	0.47	0.50	0.47	0.48	0.45	0.45	0.50	0.49	0.49	0.43						
160	0.45	0.48	0.48	0.50	0.48	0.49	0.46	0.45	0.50	0.49	0.49	0.44						
165	0.46	0.49	0.49	0.50	0.48	0.50	0.48	0.47	0.50	0.49	0.50	0.45						
170	0.47	0.50	0.49	0.50	0.49	0.50	0.49	0.48	0.50	0.49	0.50	0.47						
175	0.48	0.50	0.49	0.50	0.50	0.50	0.49	0.49	0.50	0.49	0.50	0.49						
180	0.48	0.50	0.50	0.50	0.50	0.50	0.49	0.49	0.50	0.50	0.50	0.49						

C角度范围: 0度 - 360度
C角度间隔: 30.0度
测试速度: 快速
环境温度: 25.3℃
测试人员:
测试日期: 2025-03-06


γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注:

I (cd)



1000 lm

$\kappa = 1$



F = 1000 lm
 K = 0.7
 Hcc = 0.8 m
 Hfc = 0.0 m
 Eave = 100 lx

	Pcc	Pw	Pfc
—————	70	50	30
—————	50	30	20

