



SF17 DMX Pixel Chasing RGBW Silicone LED Linear Flex

SF17-24V-5050-70-DMX4-RGBW

Specification




Technical Parameters

Electrical	
Input Voltage	24V DC
Power Consumption	18W/m
Physical	
LED Count	70 LEDs/m
Cutting Unit	7 LEDs
Cutting Unit Length	100mm
Minimum Bend Diameter	80mm
Output	
LED Light	Epistar SMD LED 5050
Color	RGW(2700K/3000K/4000K/5000K)
Working Mode	DMX (RS485)
Pixels Quantity	10 Pixels/m
IC Chips	UCS512
Max Run Length*	
Single Feed	8 M
Double Feed	16 M
Beam Angle	120°
Lumen Maintenance	70,000 Hours L70 @ 25°C 50,000 Hours L70 @ 50°C

Emitting Color		Lumen Output
	Red	32lm/m
	Green	134lm/m
	Blue	21lm/m
	RGB(White)	349lm/m
	3000K	170lm/m


Temperature Ranges	
Installation	0°C to 50°C
Operating	-40°C to 55°C
Dependability	
Warranty	5 Years Warranty
IP Rating	IP68 Wet location submersible <2m

Illuminance Distribution




SF17 DMX Pixel Chasing RGBW Silicone LED Linear Flex

Connection





SF17 Configuration and Accessories



Mold injection Connector (IP68 Factory Assembly Only)





Direct Entry Connector
MJ-SF17-D5-D02SM
MJ-SF17-D5-D03SFM




Side Entry Connector
MJ-SF17-D5-S02SM
MJ-SF17-D5-S03SFM




End Cap




Jumper
MJ-SF17-D5-D-JC






DIY Snap End Cap
DIY-SN-END-17-D-01/02




SF17 Configuration and Accessories





DIY Screw End Cap
DIY-SC-END-16





Male Connector
M12-M-5C-22AWG-D6-W-0327-S




Female Connector
M12-F-5C-22AWG-D6-W-0327-S




Front Signal & Power Connector
FR-CNR-DMX-2T1





Middle Power Connector (1 to 2)
MID-CNR-512C3-1T2





SF17 Configuration and Accessories




Middle Power Connector (2 to 2)
MID-CNR-512C3-2T2




Middle Signal Connector
MID-SIG-CNR-512C3-1T2




Positive Disconnected Connector Cable
M12-EXT-SIG-5C-20AWG-D6-W-015



Male Connector End Cap
SYZ-EC-M12-M




Female Connector End Cap
SYZ-EC-M12-F-5C




LED Linear Flex Mounting Channel


1. Aluminum Channel




ALC16S02






Installation Way




Surface Mounted




Recessed




Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
ALC16S02-035	20.40*19.60	35mm	Φ4.0mm	2	SF17
ALC16S02-100		1000mm	○4.0mm	2	SF17
ALC16S02-200		2000mm	○4.0mm	4	SF17




ALC16S08



Installation Way






Surface Mounted





Recessed

Splice Accessories




Splice Accessories: ALC16S08-SP




Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
ALC16S08-035	22.00*20.80	35mm	Φ4.0mm	2	SF17
ALC16S08-100		1000mm	○4.0mm	2	SF17
ALC16S08-200		2000mm	○4.0mm	4	SF17




LED Linear Flex Mounting Channel





Installation Way




Recessed




Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
ALC16S07-035	22.0*22.8	35mm	Φ4.0mm	2	SF17
ALC16S07-100		1000mm	○4.0mm	2	SF17
ALC16S07-200		2000mm	○4.0mm	4	SF17






Installation Way



Surface Mounted




Recessed




Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
ALC16H02-035	22.00*33.90	35mm	Φ4.0mm	2	SF17
ALC16H02-100		1000mm	○4.0mm	2	SF17
ALC16H02-200		2000mm	○4.0mm	4	SF17

LED Linear Flex Mounting Channel


2. Flexible Aluminum Channel





Dimension



Installation Way



Surface Mounted




Model	W x H(mm)	Standard Length	Suitable Product
ALC17S02FLX-05	20.4*19.60	500mm	SF17
ALC17S02FLX-10		1000mm	SF1 7


3. Plastic Channel




Dimension




Installation Way



Surface Mounted



Recessed




Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
PC16/17S02-T-100	23.53*22.90	1000mm	Φ4.0mm	2	SF17


LED Linear Flex Mounting Channel




SJJ-ZSH-008-PC



Installation Way




Surface Mounted




Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
SJJ-ZSH-008-PC	23.3*28.7	30mm	Ø4.40mm	2	SF17


4. Stainless Steel Channel




SSC16S01




Installation Way



Surface Mounted






Recessed






Model	W x H(mm)	Standard Length	Material	Screw Holes	Holes Numbers	Suitable Product
SSC16S01-05	19.35*20.03	50mm	Stainless Steel 316L	Ø4.0mm	2	SF17

LED Linear Flex Mounting Channel







Model	W x H(mm)	Standard Length	Material	Screw Holes	Holes Numbers	Suitable Product
SSC16S02-100	18.60*20.3	1000mm	Stainless Steel 316L	4.0x10mm	2	SF17



Model	W x H(mm)	Standard Length	Material	Screw Holes	Holes Numbers	Suitable Product
SSC16H01-100	18.45*33.26	1000mm	Stainless Steel 316L	4.0x10mm	2	SF17




LED Linear Flex Mounting Channel




Model	W x H(mm)	Standard Length	Material	Suitable Product
SSC16FLX01	18.00*21.80	100mm	Stainless Steel 316L	SF17
SSC16FLX03		300mm	Stainless Steel 316L	SF17
SSC16FLX05		500mm	Stainless Steel 316L	SF17
SSC16FLX10		1000mm	Stainless Steel 316L	SF17

Artflex LED Linear Flex Mounting Channel

Glare-Free Kit



Surface Mounted






Recessed




Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
AF-AG-2020-ALC16S09	22.00*24.78	1000mm	4.0x10mm	2	SF17

Artflex Kit



Surface Mounted






Recessed




Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
AF-SP-ALC16S09	22.00*24.78	1000mm	4.0x10mm	2	SF17

Artflex LED Linear Flex Mounting Channel

ColorShift Kit



Surface Mounted



Recessed



Model	W x H(mm)	Standard Length	Screw Holes	Holes Numbers	Suitable Product
AF-AG-SP-ALC16S09	22.00*24.78	1000mm	4.0x10mm	2	SF17

Product Packing Details



Standard : Carton (White Carton+Paper Reel Inside)

Product	Max.length/Reel	Carton Size	Net Weight	Gross Weight
F15/SF15	30m	35*35*19cm	12.0kg	13.6kg
F16/SF16	28m	35*35*19cm	12.9kg	14.5kg
SF17	28m	35*35*19cm	12.9kg	14.5kg
SF18	28m	35*35*19cm	12.9kg	14.5kg
F21/SF21	20m	35*35*19cm	10.4kg	12.0kg
SF10	35m	35*35*19cm	11.2kg	12.8kg
SF09	45m	35*35*19cm	7.7kg	9.3kg
SF08	60m	35*35*19cm	14.4kg	16.0kg
SF06	60m	35*35*19cm	14.4kg	16.0kg



Standard : Carton (White Carton+ Roll up packing Inside)

Product	Coiling Max. length	Quantity (Roll)	Carton Size	Net Weight	Gross Weight
SP01	10m	10	35*35*19cm	20.0kg	21.6kg
SP05	11m	10	35*35*19cm	19.8kg	21.4kg
SF05	11m	10	35*35*19cm	18.0kg	19.6kg
SF06	8m	14	35*35*19cm	26.8kg	28.4kg
SF08	8m	14	35*35*19cm	26.8kg	28.4kg
SF09	8m	10	35*35*19cm	14.4kg	16.0kg
SF10	6m	11	35*35*19cm	21.2kg	22.8kg
F15/SF15	6m	7	35*35*19cm	16.8kg	18.4kg
F16/SF16	4.5m	9	35*35*19cm	18.7kg	20.3kg
SF17	4.5m	9	35*35*19cm	18.7kg	20.3kg
SF18	4.5m	9	35*35*19cm	18.7kg	20.3kg
F21/SF21	4.5m	9	35*35*19cm	21.0kg	22.6kg
SF24	13m	2	41*41*19cm	15.6kg	17.5kg

Product Packing Details



Custom : Carton (White Box+Plastic Plate Inside)

Product	Packing 1				Packing 2			
	Packing 1 Max. Length	Quantity (Plate)	Carton Size	Gross Weight	Packing 2 Max. Length	Quantity (Plate)	Carton Size	Gross Weight
F15/SF15	5m	1	41*41*5cm	2.5kg	10m	1	57*48*6cm	5.0kg
		4	41*41*19cm	10.6kg		5	57*48*19cm	25.0kg
F16/SF16	5m	1	41*41*5cm	2.5kg	10m	1	63*53*6cm	5.0kg
		4	41*41*19cm	10.0kg		3	63*53*16cm	15.0kg
SF17	5m	1	41*41*5cm	2.5kg	10m	1	63*53*6cm	5.0kg
		4	41*41*19cm	10.6kg		3	63*53*16cm	15.0kg
SF18	5m	1	41*41*5cm	2.5kg	10m	1	63*53*6cm	5.0kg
		4	41*41*19cm	10.6kg		3	63*53*16cm	15.0kg
F21/SF21	5m	1	41*41*5cm	3.1kg	10m	1	63*53*6cm	6.2kg
		4	41*41*19cm	13.0kg		3	63*53*16cm	18.6kg
SP01	10m	1	41*41*5cm	2.6kg	20m	1	57*48*6cm	5.0kg
		4	41*41*19cm	11.0kg		5	57*48*19cm	25.0kg
SP05	10m	1	41*41*5cm	2.4kg	20m	1	57*48*6cm	3.6kg
		4	41*41*19cm	9.6kg		5	57*48*19cm	18.0kg
SF05	10m	1	41*41*5cm	2.0kg	20m	1	57*48*6cm	4.0kg
		4	41*41*19cm	8.0kg		5	57*48*19cm	20.0kg
SF06	7m	1	41*41*5cm	2.3kg	14m	1	57*48*6cm	4.4kg
		4	41*41*19cm	9.2kg		5	57*48*19cm	22.0kg
SF08	7m	1	41*41*5cm	2.3kg	14m	1	57*48*6cm	4.4kg
		4	41*41*19cm	9.2kg		5	57*48*19cm	22.0kg
SF09	9m	1	41*41*5cm	2.0kg	18m	1	57*48*6cm	3.9kg
		4	41*41*19cm	8.0kg		5	57*48*19cm	19.5kg
SF10	5m	1	41*41*5cm	2.3kg	10m	1	57*48*6cm	4.2kg
		4	41*41*19cm	9.2kg		5	57*48*19cm	21.0kg
SF24	5m	1	57*48*6cm	2.3kg	10m	1	63*53*6cm	4.2kg
		4	57*48*19cm	9.2kg		5	63*53*16cm	21.0kg
SF33	3m	1	63*53*6cm	3.4kg	10m	1	85*73*6cm	11.5kg
		3	63*53*16cm	10.2kg		2	85*73*11cm	23.0kg
SF34	3m	1	63*53*6cm	3.2kg	10m	1	85*73*6cm	11.0kg
		3	63*53*16cm	9.6kg		2	85*73*11cm	22.0kg