




SF18 Mono Color Silicone LED Linear Flex

SF18-24V-3528-144-2200K-6500K



Specification




Technical Parameters

Electrical		Optional Color		Lumen Output
Input Voltage	24V DC		2200K(2238±102K)	565lm/m
Power Consumption	10W/m		2700K(2725±145K)	656lm/m
Physical			3000K(3045±175K)	707lm/m
LED Count	144 LEDs/m		3500K(3465±245K)	642lm/m
Cutting Unit	12 LEDs		4000K(3985±275K)	817lm/m
Cutting Unit Length	83.3 mm		4500K(4503±243K)	627lm/m
Minimum Bend Diameter	120mm		5000K(5029±283K)	734lm/m
Output			6500K(6532±510K)	683lm/m
LED Light	Epistar SMD LED 3528		Green(520-530nm)	400lm/m
CRI	>80, >90		Blue (455-465nm)	80lm/m
Max Run Length*			Red (620-630nm)	160lm/m
Single Feed	10 M		Pink(610-620nm)	230lm/m
Double Feed	20 M		Amber (585-595nm)	190lm/m
Beam Angle	210°		Orange(595-605nm)	326lm/m
Temperature Ranges				
Installation	0°C to 50°C			
Operating	-40°C to 55°C			
Dependability				
Warranty	5 Years Warranty			
IP Rating	IP68 Wet location submersible <2m			

Illuminance Distribution



White Color Charts



SF18 Mono Color Silicone LED Linear Flex

Connection

