


室内灯具光度数据

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm		
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

光源数据		光度数据				光效: 4.99 lm/W
型号	5050	峰值光强(cd)	10.09	S/MH(C0/180)	1.49	
标称功率(W)		灯具效率(%)	100.0	S/MH(C90/270)	1.25	
额定电源电压(V)	24	总光通量(lm)	57.184	η UP,DN(C0-180)	13.3,37.0	
额定光通量(lm)	57.1836	CIE分类	半直接	η UP,DN(C180-360)	12.9,36.9	
灯具内光源数(只)	1	上射光通比(%)	26.1	CIBSE SHR NOM	1.50	
实测电源电压(V)		下射光通比(%)	73.9	CIBSE SHR MAX	1.55	



C角度范围: 0度 - 360度  
C角度间隔: 30.0度  
测试速度: 快速  
环境温度: 25.3℃  
测试人员:  
测试日期: 2025-03-17

γ角度范围: 0度 - 180度  
γ角度间隔: 1.0度  
测试系统: 远方(EVERFINE)GO-2000B\_V1系统 V2.00.488  
环境湿度: 65.0%  
测试距离: 6.360米 [K=1.0000]  
备注:

灯具环带光通量

环带光通量：

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ(°)	Φ环	Φ总	%lum, lamp
10	10.08	9.984	9.826	9.878	9.963	9.879	9.876	10.02	0- 10	0.9533	0.9533	1.67,1.67
20	10.02	9.686	9.269	9.607	9.838	9.622	9.328	9.734	10- 20	2.777	3.730	6.52,6.52
30	9.968	9.183	8.358	9.061	9.721	9.100	8.455	9.258	20- 30	4.342	8.072	14.1,14.1
40	9.960	8.589	7.162	8.422	9.694	8.475	7.297	8.690	30- 40	5.559	13.63	23.8,23.8
50	9.977	7.830	5.795	7.620	9.585	7.685	5.959	7.942	40- 50	6.319	19.95	34.9,34.9
60	9.306	6.924	4.385	6.704	8.863	6.771	4.532	7.044	50- 60	6.565	26.52	46.4,46.4
70	8.248	5.973	2.955	5.625	7.764	5.666	3.070	6.076	60- 70	6.232	32.75	57.3,57.3
80	6.974	4.716	1.550	4.366	6.308	4.399	1.637	4.799	70- 80	5.376	38.12	66.7,66.7
90	6.194	3.676	0.3121	3.301	5.436	3.234	0.3156	3.665	80- 90	4.124	42.25	73.9,73.9
100	6.568	3.658	0.3207	3.431	5.620	3.335	0.2889	3.665	90-100	3.699	45.95	80.3,80.3
110	5.938	2.970	0.3236	3.279	5.576	3.221	0.2947	3.178	100-110	3.498	49.44	86.5,86.5
120	5.024	2.505	0.3294	2.795	4.659	2.739	0.2976	2.608	110-120	2.879	52.32	91.5,91.5
130	3.822	2.097	0.3323	2.241	3.719	2.192	0.2976	2.131	120-130	2.137	54.46	95.2,95.2
140	2.908	1.267	0.3352	1.646	2.761	1.605	0.2832	1.324	130-140	1.401	55.86	97.7,97.7
150	1.789	0.8234	0.3352	1.070	1.752	1.046	0.2832	0.8071	140-150	0.7741	56.64	99,99
160	1.108	0.5277	0.3351	0.6755	0.9999	0.6592	0.2860	0.5229	150-160	0.3716	57.01	99.7,99.7
170	0.3896	0.3750	0.3323	0.4273	0.4006	0.4241	0.3034	0.3668	160-170	0.1419	57.15	99.9,99.9
180	0.3403	0.3375	0.3323	0.3379	0.3403	0.3418	0.3207	0.3350	170-180	0.0350	57.18	100,100
单位:°	光强:cd									单位:lm		

锥面光通量(90度)：16.725 lm

%lum = 29.2%  
%lamp = 29.2%


锥面光通量(130度)：29.705 lm

%lum = 51.9%  
%lamp = 51.9%

C角度范围： 0度 - 360度 C角度间隔： 30.0度 测试速度： 快速 环境温度:25.3℃ 测试人员： 测试日期:2025-03-17	γ角度范围： 0度 - 180度 γ角度间隔： 1.0度 测试系统： 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注：
--	---

灯具亮度限制曲线

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm		
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



平均亮度值 cd/(m2)		
γ (°)	C0/180	C90/270
85	4424	601
80	2436	541
75	1783	527
70	1463	523
65	1268	526
60	1129	531
55	1031	538
50	942	546
45	857	556


C角度范围: 0度 - 360度  
C角度间隔: 30.0度  
测试速度: 快速  
环境温度:25.3℃  
测试人员:  
测试日期:2025-03-17

γ角度范围: 0度 - 180度  
γ角度间隔: 1.0度  
测试系统: 远方 (EVERFINE) GO-2000B\_V1 系统 V2.00.488  
环境湿度:65.0%  
测试距离:6.360米 [K=1.0000]  
备注:

工作面利用系数和灯具概算曲线

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm		
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	工 作 面 利 用 系 数															
0.0	1.13	1.13	1.13	1.07	1.07	1.07	.97	.97	.97	.87	.87	.87	.78	.78	.78	.74
1.0	.94	.88	.84	.89	.84	.80	.80	.76	.72	.71	.68	.66	.64	.61	.59	.55
2.0	.80	.72	.65	.76	.69	.63	.68	.62	.57	.61	.56	.52	.54	.50	.47	.43
3.0	.69	.60	.53	.65	.57	.51	.59	.52	.47	.52	.47	.42	.47	.42	.39	.35
4.0	.61	.51	.44	.57	.49	.42	.52	.44	.39	.46	.40	.35	.41	.36	.32	.29
5.0	.54	.44	.37	.51	.42	.36	.46	.38	.33	.41	.35	.30	.37	.32	.28	.25
6.0	.48	.39	.32	.45	.37	.31	.41	.34	.28	.37	.31	.26	.33	.28	.24	.21
7.0	.43	.34	.28	.41	.33	.27	.37	.30	.25	.33	.27	.23	.30	.25	.21	.18
8.0	.39	.30	.24	.37	.29	.24	.34	.27	.22	.30	.25	.20	.27	.22	.19	.16
9.0	.36	.27	.22	.34	.26	.21	.31	.24	.19	.28	.22	.18	.25	.20	.17	.14
10.0	.33	.25	.19	.31	.24	.19	.28	.22	.17	.26	.20	.16	.23	.18	.15	.13



C角度范围: 0度 - 360度  
C角度间隔: 30.0度  
测试速度: 快速  
环境温度: 25.3℃  
测试人员:  
测试日期: 2025-03-17

γ角度范围: 0度 - 180度  
γ角度间隔: 1.0度  
测试系统: 远方(EVERFINE) GO-2000B\_V1 系统 V2.00.488  
环境湿度: 65.0%  
测试距离: 6.360米 [K=1.0000]  
备注:

墙面和天花板利用系数

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm					
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B			灯具类型:		灯具重量:
灯具规格:			外型尺寸: Length=1m		测试编号:
制造厂商: OLympia lighting			发光口面:		遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	墙 壁 面 利 用 系 数															
0.0																
1.0	.384	.219	.069	.369	.211	.067	.341	.195	.062	.315	.181	.058	.291	.168	.054	
2.0	.332	.182	.056	.319	.176	.054	.293	.163	.051	.269	.151	.047	.247	.140	.044	
3.0	.295	.157	.047	.283	.151	.046	.259	.140	.043	.238	.130	.040	.217	.120	.037	
4.0	.265	.138	.041	.254	.133	.039	.233	.123	.037	.213	.114	.034	.195	.106	.032	
5.0	.241	.123	.036	.231	.118	.035	.211	.110	.032	.193	.102	.030	.176	.094	.028	
6.0	.221	.111	.032	.211	.107	.031	.194	.099	.029	.177	.092	.027	.161	.085	.025	
7.0	.204	.101	.029	.195	.097	.028	.178	.090	.026	.163	.084	.024	.149	.077	.023	
8.0	.189	.092	.026	.181	.089	.025	.166	.083	.024	.151	.077	.022	.138	.071	.021	
9.0	.176	.085	.024	.168	.082	.023	.154	.076	.022	.141	.071	.020	.129	.065	.019	
10.0	.164	.079	.022	.158	.076	.021	.145	.071	.020	.132	.066	.019	.121	.061	.017	

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	天花板利用系数															
0.0	.389	.389	.389	.333	.333	.333	.227	.227	.227	.131	.131	.131	.042	.042	.042	
1.0	.386	.356	.329	.330	.306	.283	.226	.210	.196	.130	.122	.114	.042	.039	.037	
2.0	.380	.334	.295	.325	.287	.255	.223	.199	.178	.129	.116	.104	.041	.037	.034	
3.0	.372	.318	.274	.319	.274	.237	.219	.190	.167	.127	.111	.098	.041	.036	.032	
4.0	.365	.305	.260	.313	.264	.226	.215	.184	.159	.125	.108	.094	.040	.035	.031	
5.0	.357	.296	.250	.307	.256	.218	.211	.179	.154	.122	.105	.091	.039	.034	.030	
6.0	.350	.288	.243	.301	.249	.212	.208	.175	.150	.120	.103	.089	.039	.034	.029	
7.0	.343	.281	.238	.295	.244	.208	.204	.171	.147	.118	.101	.088	.038	.033	.029	
8.0	.336	.276	.235	.290	.239	.205	.200	.168	.145	.117	.099	.086	.038	.033	.029	
9.0	.330	.271	.232	.284	.235	.202	.197	.166	.143	.115	.098	.086	.037	.032	.028	
10.0	.324	.267	.229	.280	.232	.200	.194	.163	.142	.113	.097	.085	.037	.032	.028	

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度: 25.3℃ 测试人员: 测试日期: 2025-03-17	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度: 65.0% 测试距离: 6.360米 [K=1.0000] 备注:
--	---

UGR(Unified Glare Rating)数据表

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm										
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B					灯具类型:			灯具重量:		
灯具规格:					外型尺寸: Length=1m			测试编号:		
制造厂商: OLympia lighting					发光口面:			遮光角:		
反射比: 天花板	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
墙面	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
房间尺寸	横向(Viewed crosswise)					纵向(Viewed endwise)				
x = 2H y = 2H	21.8	23.1	22.4	23.8	24.5	18.6	19.9	19.3	20.6	21.3
3H	24.7	25.9	25.3	26.5	27.3	20.4	21.6	21.0	22.2	23.0
4H	26.2	27.3	26.8	28.0	28.7	21.2	22.3	21.8	23.0	23.7
6H	27.8	28.9	28.5	29.5	30.4	21.8	22.9	22.5	23.6	24.4
8H	28.7	29.7	29.4	30.4	31.2	22.1	23.1	22.8	23.8	24.6
12H	29.7	30.7	30.4	31.4	32.3	22.3	23.3	23.0	24.0	24.8
4H 2H	22.3	23.5	23.0	24.1	24.9	20.1	21.2	20.7	21.9	22.6
3H	25.4	26.4	26.1	27.1	27.9	22.0	23.0	22.7	23.7	24.5
4H	27.1	28.0	27.8	28.7	29.6	23.0	23.9	23.7	24.6	25.5
6H	29.0	29.8	29.7	30.5	31.4	23.8	24.6	24.6	25.4	26.3
8H	30.0	30.7	30.7	31.5	32.4	24.2	24.9	24.9	25.7	26.6
12H	31.2	31.9	31.9	32.6	33.6	24.5	25.2	25.2	25.9	26.9
8H 4H	27.4	28.2	28.2	28.9	29.8	24.2	24.9	24.9	25.7	26.6
6H	29.6	30.2	30.3	31.0	31.9	25.4	26.0	26.2	26.8	27.7
8H	30.8	31.4	31.6	32.2	33.1	25.9	26.5	26.7	27.3	28.3
12H	32.2	32.7	33.0	33.5	34.5	26.4	26.9	27.2	27.7	28.7
12H 4H	27.4	28.1	28.2	28.9	29.8	24.6	25.3	25.3	26.0	27.0
6H	29.7	30.2	30.5	31.0	32.0	26.0	26.5	26.8	27.3	28.3
8H	31.0	31.5	31.8	32.3	33.3	26.7	27.2	27.5	28.0	29.0
不同间隔布灯时,观察者位置引起的UGR变化(CIE Pub.117):										
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.4				

依据CIE Pub.117计算, 57.181m光源光通表格中的数据需要进行修正(81log(F/F0) = -9.9).  
出光口面积: 0.0165 m2

C角度范围: 0度 - 360度	γ角度范围: 0度 - 180度
C角度间隔: 30.0度	γ角度间隔: 1.0度
测试速度: 快速	测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境温度:25.3℃	环境湿度:65.0%
测试人员:	测试距离:6.360米 [K=1.0000]
测试日期:2025-03-17	备注:

UF利用系数表

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm		
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:


反 射 比 / REFLECTANCE										
天花板	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
墙壁	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
室形指数	利用系数 UTILIZATION FACTORS(%) k(RI) x RCR = 5									
k = 0.60	45	32	25	43	32	25	41	30	24	17
0.80	54	40	32	52	40	32	49	38	31	22
1.00	61	48	40	59	47	39	55	47	37	28
1.25	68	55	47	66	54	45	60	50	43	33
1.50	74	61	52	70	59	51	65	55	48	36
2.00	81	70	61	77	67	59	71	62	56	42
2.50	86	75	67	82	72	65	74	67	60	46
3.00	89	80	72	85	77	70	77	70	65	49
4.00	94	86	79	90	82	76	81	75	70	54
5.00	97	90	84	93	86	81	84	79	74	57
ROOM INDEX	UF (总)									UF (直接)
依据标准文件 DIN EN 13032-2 2004			悬挂灯				安装距高比 SHR <sub>NOM</sub> = 1.25			

C角度范围: 0度 - 360度  
C角度间隔: 30.0度  
测试速度: 快速  
环境温度: 25.3℃  
测试人员:  
测试日期: 2025-03-17

γ角度范围: 0度 - 180度  
γ角度间隔: 1.0度  
测试系统: 远方(EVERFINE) GO-2000B\_V1 系统 V2.00.488  
环境湿度: 65.0%  
测试距离: 6.360米 [K=1.0000]  
备注:

灯 具 等 光 强 曲 线

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm		
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度  
C角度间隔: 30.0度  
测试速度: 快速  
环境温度:25.3℃  
测试人员:  
测试日期:2025-03-17

γ角度范围: 0度 - 180度  
γ角度间隔: 1.0度  
测试系统: 远方 (EVERFINE) GO-2000B\_V1 系统 V2.00.488  
环境湿度:65.0%  
测试距离:6.360米 [K=1.0000]  
备注:



灯 具 有 效 平 均 照 度 图

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm		
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:




C角度范围: 0度 - 360度  
C角度间隔: 30.0度  
测试速度: 快速  
环境温度:25.3℃  
测试人员:  
测试日期:2025-03-17

γ角度范围: 0度 - 180度  
γ角度间隔: 1.0度  
测试系统: 远方(EVERFINE)GO-2000B\_V1系统 V2.00.488  
环境湿度:65.0%  
测试距离:6.360米 [K=1.0000]  
备注:

平面等照度曲线

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm		
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:



C角度范围: 0度 - 360度  
C角度间隔: 30.0度  
测试速度: 快速  
环境温度: 25.3℃  
测试人员:  
测试日期: 2025-03-17

γ角度范围: 0度 - 180度  
γ角度间隔: 1.0度  
测试系统: 远方 (EVERFINE) GO-2000B\_V1 系统 V2.00.488  
环境湿度: 65.0%  
测试距离: 6.360米 [K=1.0000]  
备注:

LED筒灯平均亮度报告


实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm		
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商: OLympia lighting	发光口面:	遮光角:

平均亮度	数值 (cd/m2)
L横 (65) av	1229
L横 (75) av	1715
L横 (85) av	4163
L纵 (65) av	536
L纵 (75) av	539
L纵 (85) av	628
L45 (65) av	915
L45 (75) av	1238
L45 (85) av	2739

注: 依据标准 GB/T 29293-2012 计算

C角度范围: 0度 - 360度 C角度间隔: 30.0度 测试速度: 快速 环境温度: 25.3℃ 测试人员: 测试日期: 2025-03-17	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度: 65.0% 测试距离: 6.360米 [K=1.0000] 备注:
--	--

平面照度曲线



C角度范围: 0度 - 360度  
C角度间隔: 30.0度  
测试速度: 快速  
环境温度: 25.3℃  
测试人员:  
测试日期: 2025-03-17

γ角度范围: 0度 - 180度  
γ角度间隔: 1.0度  
测试系统: 远方 (EVERFINE) GO-2000B\_V1 系统 V2.00.488  
环境湿度: 65.0%  
测试距离: 6.360米 [K=1.0000]  
备注:

光 强 分 布 数 据 表 格

实测参数: U:24.00V I:0.4771A P:11.45W PF:1.000 Freq:0Hz 实检光通: 57.1836x1 lm																	
灯具名称: SF18-24V-5050-70-SPI-RGBW(2700K)-B									灯具类型:						灯具重量:		
灯具规格:									外型尺寸: Length=1m						测试编号:		
制造厂商: OLympia lighting									发光口面:						遮光角:		


表--1单位: cd

C (DEG) γ (DEG)	0	30	60	90	120	150	180	210	240	270	300	330						
0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0						
5	10.1	10.0	10.0	9.97	10.00	9.98	9.99	9.99	9.99	10.0	10.0	10.1						
10	10.1	10.0	9.96	9.83	9.86	9.89	9.96	9.90	9.86	9.88	9.96	10.1						
15	10.1	9.94	9.78	9.60	9.65	9.87	9.96	9.88	9.65	9.65	9.78	10.0						
20	10.0	9.85	9.52	9.27	9.46	9.75	9.84	9.78	9.47	9.33	9.54	9.93						
25	9.92	9.67	9.23	8.86	9.20	9.49	9.69	9.53	9.22	8.93	9.27	9.76						
30	9.97	9.48	8.88	8.36	8.82	9.30	9.72	9.34	8.86	8.46	8.94	9.58						
35	10.0	9.42	8.44	7.79	8.33	9.21	9.73	9.24	8.39	7.91	8.51	9.52						
40	9.96	9.23	7.94	7.16	7.80	9.04	9.69	9.08	7.87	7.30	8.03	9.35						
45	9.99	8.99	7.39	6.49	7.25	8.84	9.63	8.87	7.33	6.65	7.49	9.11						
50	9.98	8.85	6.81	5.79	6.66	8.58	9.58	8.62	6.75	5.96	6.92	8.96						
55	9.75	8.63	6.15	5.10	6.02	8.27	9.38	8.31	6.11	5.25	6.28	8.75						
60	9.31	8.24	5.60	4.38	5.45	7.96	8.86	8.01	5.52	4.53	5.72	8.37						
65	8.83	7.82	5.09	3.67	4.92	7.41	8.31	7.48	4.98	3.80	5.20	7.93						
70	8.25	7.31	4.63	2.95	4.42	6.83	7.76	6.87	4.45	3.07	4.73	7.42						
75	7.61	6.59	4.12	2.25	3.90	6.19	7.04	6.22	3.94	2.35	4.22	6.69						
80	6.97	5.92	3.51	1.55	3.31	5.42	6.31	5.45	3.35	1.64	3.60	6.00						
85	6.36	5.28	2.84	0.87	2.65	4.69	5.62	4.69	2.67	0.94	2.91	5.33						
90	6.19	5.02	2.33	0.31	2.22	4.38	5.44	4.31	2.15	0.32	2.33	5.00						
95	6.40	5.26	2.33	0.32	2.13	4.53	5.59	4.40	2.07	0.29	2.32	5.22						
100	6.57	5.37	1.94	0.32	2.06	4.80	5.62	4.67	2.00	0.29	1.97	5.36						
105	6.43	4.91	1.77	0.32	2.02	4.82	5.66	4.77	1.95	0.29	1.81	5.07						
110	5.94	4.53	1.41	0.32	2.01	4.54	5.58	4.50	1.94	0.29	1.65	4.70						
115	5.49	4.12	1.59	0.33	1.99	4.13	5.17	4.09	1.91	0.30	1.68	4.19						
120	5.02	3.58	1.42	0.33	1.84	3.75	4.66	3.71	1.76	0.30	1.48	3.73						
125	4.49	3.32	1.22	0.33	1.66	3.40	4.17	3.38	1.59	0.30	1.28	3.43						
130	3.82	3.07	1.12	0.33	1.43	3.05	3.72	3.03	1.35	0.30	1.19	3.07						
135	3.46	2.22	0.94	0.33	1.24	2.65	3.26	2.65	1.16	0.29	0.97	2.36						
140	2.91	1.71	0.82	0.34	1.05	2.24	2.76	2.23	0.98	0.28	0.81	1.84						
145	2.36	1.29	0.70	0.34	0.89	1.79	2.26	1.79	0.81	0.28	0.67	1.43						
150	1.79	1.05	0.60	0.34	0.72	1.42	1.75	1.44	0.65	0.28	0.53	1.08						
155	1.40	0.83	0.50	0.34	0.60	1.12	1.36	1.14	0.54	0.28	0.44	0.92						
160	1.11	0.62	0.44	0.34	0.51	0.84	1.00	0.85	0.47	0.29	0.39	0.66						
165	0.70	0.44	0.39	0.33	0.44	0.60	0.69	0.62	0.40	0.29	0.35	0.46						
170	0.39	0.37	0.38	0.33	0.41	0.45	0.40	0.47	0.38	0.30	0.34	0.39						
175	0.36	0.35	0.36	0.33	0.39	0.39	0.35	0.41	0.36	0.31	0.33	0.36						
180	0.34	0.34	0.34	0.33	0.34	0.34	0.34	0.35	0.34	0.32	0.33	0.34						

C角度范围: 0度 - 360度  
C角度间隔: 30.0度  
测试速度: 快速  
环境温度: 25.3℃  
测试人员:  
测试日期: 2025-03-17


γ角度范围: 0度 - 180度  
γ角度间隔: 1.0度  
测试系统: 远方 (EVERFINE) GO-2000B\_V1 系统 V2.00.488  
环境湿度: 65.0%  
测试距离: 6.360米 [K=1.0000]  
备注:

I (cd)



1000 lm

$\kappa = 1$



F = 1000 lm  
 K = 0.7  
 Hcc = 0.8 m  
 Hfc = 0.0 m  
 Eave = 100 lx

	Pcc	Pw	Pfc
—————	70	50	30
—————	50	30	20

