


室内灯具光度数据

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm		
灯具名称: SF18-24V-5050-72-RGBW (2700K) -80	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商:	发光口面:	遮光角:

光源数据		光度数据				光效: 20.01 lm/W
型号		峰值光强 (cd)	11.86	S/MH (C0/180)	1.72	
标称功率 (W)		灯具效率 (%)	100.0	S/MH (C90/270)	1.25	
额定电源电压 (V)		总光通量 (lm)	68.439	η UP, DN (C0-180)	12.9, 37.2	
额定光通量 (lm)	68.439	CIE分类	半直接	η UP, DN (C180-360)	12.8, 37.1	
灯具内光源数 (只)	1	上射光通比 (%)	25.7	CIBSE SHR NOM	1.50	
实测电源电压 (V)		下射光通比 (%)	74.3	CIBSE SHR MAX	1.55	



C角度范围: 0度 - 360度
C角度间隔: 22.5度
测试速度: 快速
环境温度: 25.3℃
测试人员: Cloud
测试日期: 2024-10-15

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注: RED

灯具环带光通量

环带光通量：

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ(°)	Φ环	Φ总	%lum, lamp
10	10.80	10.52	10.17	10.72	10.97	10.67	10.11	10.53	0- 10	0.9995	0.9995	1.46,1.46
20	11.26	10.67	9.640	10.89	11.50	10.80	9.534	10.61	10- 20	3.012	4.012	5.86,5.86
30	11.51	10.56	8.770	10.81	11.84	10.67	8.635	10.43	20- 30	4.887	8.899	13,13
40	11.52	10.17	7.623	10.43	11.83	10.27	7.463	9.992	30- 40	6.418	15.32	22.4,22.4
50	11.21	9.509	6.273	9.743	11.52	9.613	6.110	9.342	40- 50	7.444	22.76	33.3,33.3
60	10.59	8.612	4.801	8.811	10.90	8.708	4.650	8.462	50- 60	7.867	30.63	44.8,44.8
70	9.756	7.519	3.283	7.645	9.999	7.617	3.167	7.371	60- 70	7.673	38.30	56,56
80	8.533	6.290	1.774	6.353	8.823	6.371	1.692	6.153	70- 80	6.897	45.20	66,66
90	7.290	4.989	0.3538	5.100	7.583	5.140	0.3151	4.896	80- 90	5.667	50.87	74.3,74.3
100	6.836	4.662	0.3469	4.796	7.110	4.846	0.3122	4.587	90-100	4.827	55.69	81.4,81.4
110	6.025	3.751	0.3700	4.315	6.508	4.332	0.3267	3.219	100-110	4.214	59.91	87.5,87.5
120	5.094	3.079	0.3701	3.516	5.519	3.515	0.3412	2.793	110-120	3.329	63.24	92.4,92.4
130	3.993	2.183	0.3730	2.633	4.288	2.627	0.3499	1.962	120-130	2.388	65.62	95.9,95.9
140	2.851	1.423	0.3730	1.741	3.042	1.738	0.3672	1.335	130-140	1.512	67.14	98.1,98.1
150	1.845	0.8803	0.3730	0.9587	1.805	0.9569	0.3788	0.7758	140-150	0.7992	67.94	99.3,99.3
160	0.9373	0.4906	0.3730	0.4245	0.7223	0.4123	0.3816	0.4356	150-160	0.3423	68.28	99.8,99.8
170	0.3988	0.3952	0.3730	0.3953	0.3873	0.3981	0.3816	0.3924	160-170	0.1238	68.40	99.9,99.9
180	0.3902	0.3952	0.3787	0.3953	0.3873	0.3981	0.3816	0.3895	170-180	0.0373	68.44	100,100
单位:°	光强:cd									单位:lm		

锥面光通量(90度)：18.947 lm

%lum = 27.7%
%lamp = 27.7%


锥面光通量(130度)：34.526 lm

%lum = 50.4%
%lamp = 50.4%

C角度范围： 0度 - 360度 C角度间隔：22.5度 测试速度：快速 环境温度:25.3℃ 测试人员:Cloud 测试日期:2024-10-15	γ角度范围： 0度 - 180度 γ角度间隔： 1.0度 测试系统：远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注：RED
---	---

灯具亮度限制曲线

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm		
灯具名称: SF18-24V-5050-72-RGBW (2700K) -80	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商:	发光口面:	遮光角:



平均亮度值 cd/(m2)		
γ (°)	C0/180	C90/270
85	5311	693
80	2887	600
75	2078	572
70	1675	564
65	1418	561
60	1244	564
55	1119	568
50	1024	573
45	947	579


C角度范围: 0度 - 360度
C角度间隔: 22.5度
测试速度: 快速
环境温度: 25.3℃
测试人员: Cloud
测试日期: 2024-10-15

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注: RED

工作面利用系数和灯具概算曲线

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm		
灯具名称: SF18-24V-5050-72-RGBW (2700K)-80	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商:	发光口面:	遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	工 作 面 利 用 系 数															
0.0	1.13	1.13	1.13	1.07	1.07	1.07	.97	.97	.97	.87	.87	.87	.78	.78	.78	.74
1.0	.93	.87	.82	.88	.83	.79	.79	.75	.71	.71	.68	.65	.63	.61	.58	.54
2.0	.79	.71	.64	.75	.68	.61	.67	.61	.56	.60	.55	.51	.53	.49	.46	.42
3.0	.68	.59	.52	.65	.56	.49	.58	.51	.45	.52	.46	.41	.46	.41	.37	.34
4.0	.60	.50	.43	.56	.48	.41	.51	.43	.38	.45	.39	.34	.40	.35	.31	.28
5.0	.53	.43	.36	.50	.41	.34	.45	.37	.32	.40	.34	.29	.36	.31	.26	.24
6.0	.47	.37	.31	.45	.36	.30	.40	.33	.27	.36	.30	.25	.32	.27	.23	.20
7.0	.42	.33	.27	.40	.32	.26	.36	.29	.24	.33	.26	.22	.29	.24	.20	.17
8.0	.38	.29	.23	.36	.28	.23	.33	.26	.21	.30	.24	.19	.27	.21	.18	.15
9.0	.35	.26	.21	.33	.25	.20	.30	.23	.19	.27	.21	.17	.25	.19	.16	.14
10.0	.32	.24	.18	.30	.23	.18	.28	.21	.17	.25	.19	.15	.23	.18	.14	.12



C角度范围: 0度 - 360度
C角度间隔: 22.5度
测试速度: 快速
环境温度: 25.3℃
测试人员: Cloud
测试日期: 2024-10-15

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注: RED

墙面和天花板利用系数

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm					
灯具名称: SF18-24V-5050-72-RGBW(2700K)-80			灯具类型:		灯具重量:
灯具规格:			外型尺寸: Length=1m		测试编号:
制造厂商:			发光口面:		遮光角:

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	墙 壁 面 利 用 系 数															
0.0																
1.0	.400	.228	.072	.385	.220	.070	.357	.205	.065	.331	.191	.061	.307	.178	.057	
2.0	.342	.188	.058	.329	.181	.056	.303	.169	.052	.279	.157	.049	.258	.146	.046	
3.0	.302	.161	.048	.290	.155	.047	.266	.144	.044	.245	.134	.041	.225	.125	.039	
4.0	.271	.141	.041	.259	.136	.040	.238	.126	.038	.219	.117	.035	.200	.109	.033	
5.0	.245	.125	.036	.235	.121	.035	.216	.112	.033	.198	.104	.031	.181	.097	.029	
6.0	.224	.112	.032	.215	.108	.031	.197	.101	.029	.180	.094	.028	.165	.087	.026	
7.0	.206	.102	.029	.198	.098	.028	.181	.092	.026	.166	.085	.025	.152	.079	.023	
8.0	.191	.093	.026	.183	.090	.025	.168	.084	.024	.154	.078	.022	.141	.072	.021	
9.0	.178	.086	.024	.170	.083	.023	.157	.077	.022	.143	.072	.021	.131	.067	.019	
10.0	.166	.080	.022	.159	.077	.021	.146	.072	.020	.134	.067	.019	.123	.062	.018	

顶棚	80%			70%			50%			30%			10%			0
墙面	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
地板	20%			20%			20%			20%			20%			0
室空间比	天花板利用系数															
0.0	.386	.386	.386	.330	.330	.330	.225	.225	.225	.129	.129	.129	.041	.041	.041	
1.0	.384	.353	.324	.328	.303	.279	.225	.208	.193	.129	.120	.112	.041	.039	.036	
2.0	.378	.330	.290	.323	.284	.251	.222	.197	.175	.128	.114	.103	.041	.037	.033	
3.0	.370	.314	.269	.317	.271	.234	.218	.188	.164	.126	.110	.097	.040	.036	.032	
4.0	.363	.302	.256	.311	.261	.222	.214	.182	.156	.124	.107	.093	.040	.035	.030	
5.0	.355	.292	.246	.305	.253	.214	.210	.177	.151	.122	.104	.090	.039	.034	.030	
6.0	.348	.285	.239	.299	.247	.209	.206	.173	.148	.120	.102	.088	.039	.033	.029	
7.0	.341	.278	.235	.293	.241	.204	.202	.169	.145	.118	.100	.086	.038	.033	.029	
8.0	.334	.273	.231	.287	.237	.201	.199	.166	.143	.116	.098	.085	.037	.032	.028	
9.0	.328	.268	.228	.282	.233	.199	.196	.164	.141	.114	.097	.084	.037	.032	.028	
10.0	.322	.264	.226	.277	.229	.197	.192	.161	.140	.112	.095	.083	.036	.031	.028	

C角度范围: 0度 - 360度 C角度间隔: 22.5度 测试速度: 快速 环境温度:25.3℃ 测试人员:Cloud 测试日期:2024-10-15	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注: RED
---	---

UGR(Unified Glare Rating)数据表

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm										
灯具名称: SF18-24V-5050-72-RGBW (2700K)-80					灯具类型:			灯具重量:		
灯具规格:					外型尺寸: Length=1m			测试编号:		
制造厂商:					发光口面:			遮光角:		
反射比: 天花板	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
墙面	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
房间尺寸	横向(Viewed crosswise)					纵向(Viewed endwise)				
x = 2H y = 2H	21.6	23.0	22.2	23.6	24.3	18.7	20.0	19.3	20.6	21.3
3H	24.6	25.8	25.2	26.4	27.2	20.4	21.6	21.0	22.3	23.0
4H	26.1	27.3	26.8	28.0	28.7	21.2	22.3	21.8	23.0	23.8
6H	27.9	28.9	28.5	29.6	30.4	21.9	22.9	22.5	23.6	24.4
8H	28.8	29.9	29.5	30.6	31.4	22.1	23.2	22.8	23.9	24.7
12H	29.9	30.9	30.6	31.6	32.4	22.4	23.4	23.1	24.1	24.9
4H 2H	22.2	23.4	22.9	24.0	24.8	20.2	21.3	20.8	22.0	22.8
3H	25.4	26.4	26.1	27.1	27.9	22.2	23.2	22.9	23.9	24.7
4H	27.2	28.1	27.9	28.8	29.7	23.2	24.1	23.9	24.8	25.7
6H	29.1	29.9	29.8	30.7	31.6	24.1	24.9	24.8	25.6	26.5
8H	30.2	30.9	30.9	31.7	32.6	24.4	25.2	25.2	26.0	26.9
12H	31.4	32.1	32.1	32.9	33.8	24.7	25.4	25.5	26.2	27.1
8H 4H	27.5	28.3	28.3	29.0	29.9	24.5	25.3	25.2	26.0	26.9
6H	29.8	30.4	30.5	31.2	32.1	25.8	26.4	26.5	27.2	28.1
8H	31.1	31.6	31.8	32.4	33.4	26.4	26.9	27.1	27.7	28.7
12H	32.5	33.0	33.3	33.9	34.8	26.9	27.4	27.7	28.2	29.2
12H 4H	27.5	28.3	28.3	29.0	29.9	24.9	25.6	25.7	26.4	27.3
6H	29.9	30.5	30.7	31.3	32.2	26.4	27.0	27.2	27.8	28.8
8H	31.3	31.8	32.1	32.6	33.6	27.2	27.7	28.0	28.5	29.5
不同间隔布灯时,观察者位置引起的UGR变化(CIE Pub.117):										
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.5				

依据CIE Pub.117计算, 68.44lm光源光通表格中的数据需要进行修正(8log(F/F0) = -9.3).
出光口面积: 0.017 m2

C角度范围: 0度 - 360度	γ角度范围: 0度 - 180度
C角度间隔: 22.5度	γ角度间隔: 1.0度
测试速度: 快速	测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境温度:25.3℃	环境湿度:65.0%
测试人员:Cloud	测试距离:6.360米 [K=1.0000]
测试日期:2024-10-15	备注: RED

UF利用系数表

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm		
灯具名称: SF18-24V-5050-72-RGBW(2700K)-80	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商:	发光口面:	遮光角:


反 射 比 / REFLECTANCE										
天花板	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
墙壁	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
工作面	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
室形指数	利用系数 UTILIZATION FACTORS(%) k(RI) x RCR = 5									
k = 0.60	44	31	24	43	31	23	40	29	23	16
0.80	53	39	31	51	38	31	48	37	30	21
1.00	60	47	38	58	46	37	54	46	36	26
1.25	67	54	45	65	52	44	60	49	42	31
1.50	73	60	51	69	58	49	64	54	47	35
2.00	80	68	59	77	66	58	70	61	54	41
2.50	85	74	65	81	71	63	74	66	59	45
3.00	89	79	71	85	76	68	77	70	64	48
4.00	94	85	78	89	82	75	81	75	69	53
5.00	97	89	83	92	85	80	83	78	73	56
ROOM INDEX	UF (总)									UF (直接)
依据标准文件 DIN EN 13032-2 2004			悬挂灯				安装距高比 SHR _{NOM} = 1.25			

C角度范围: 0度 - 360度
C角度间隔: 22.5度
测试速度: 快速
环境温度:25.3℃
测试人员:Cloud
测试日期:2024-10-15

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方(EVERFINE)GO-2000B_V1系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注: RED

灯 具 等 光 强 曲 线

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm		
灯具名称: SF18-24V-5050-72-RGBW (2700K) -80	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商:	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 22.5度
测试速度: 快速
环境温度:25.3℃
测试人员:Cloud
测试日期:2024-10-15

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注: RED

灯 具 有 效 平 均 照 度 图

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm		
灯具名称: SF18-24V-5050-72-RGBW (2700K)-80	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商:	发光口面:	遮光角:




C角度范围: 0度 - 360度
C角度间隔: 22.5度
测试速度: 快速
环境温度:25.3℃
测试人员:Cloud
测试日期:2024-10-15

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度:65.0%
测试距离:6.360米 [K=1.0000]
备注: RED

平面等照度曲线

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm		
灯具名称: SF18-24V-5050-72-RGBW (2700K) -80	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商:	发光口面:	遮光角:



C角度范围: 0度 - 360度
C角度间隔: 22.5度
测试速度: 快速
环境温度: 25.3℃
测试人员: Cloud
测试日期: 2024-10-15

γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注: RED

LED筒灯平均亮度报告


实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm		
灯具名称: SF18-24V-5050-72-RGBW(2700K)-80	灯具类型:	灯具重量:
灯具规格:	外型尺寸: Length=1m	测试编号:
制造厂商:	发光口面:	遮光角:

平均亮度	数值 (cd/m2)
L横 (65) av	1439
L横 (75) av	2114
L横 (85) av	5410
L纵 (65) av	553
L纵 (75) av	563
L纵 (85) av	671
L45 (65) av	1131
L45 (75) av	1575
L45 (85) av	3788

注:依据标准 GB/T 29293-2012 计算

C角度范围: 0度 - 360度 C角度间隔: 22.5度 测试速度: 快速 环境温度:25.3℃ 测试人员:Cloud 测试日期:2024-10-15	γ角度范围: 0度 - 180度 γ角度间隔: 1.0度 测试系统: 远方(EVERFINE) GO-2000B_V1 系统 V2.00.488 环境湿度:65.0% 测试距离:6.360米 [K=1.0000] 备注: RED
---	---

平面照度曲线



C角度范围: 0度 - 360度
C角度间隔: 22.5度
测试速度: 快速
环境温度: 25.3℃
测试人员: Cloud
测试日期: 2024-10-15

Y角度范围: 0度 - 180度
Y角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注: RED

光 强 分 布 数 据 表 格

实测参数: U:24.00V I:0.1425A P:3.420W PF:1.000 Freq:0Hz 实检光通: 68.439x1 lm																	
灯具名称: SF18-24V-5050-72-RGBW (2700K) -80									灯具类型:						灯具重量:		
灯具规格:									外型尺寸: Length=1m						测试编号:		
制造厂商:									发光口面:						遮光角:		


表--1单位: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3			
5	10.5	10.5	10.3	10.3	10.3	10.4	10.5	10.6	10.6	10.6	10.5	10.4	10.3	10.3	10.4	10.4			
10	10.8	10.8	10.5	10.3	10.2	10.4	10.7	10.9	11.0	10.9	10.7	10.4	10.1	10.2	10.5	10.7			
15	11.0	11.0	10.6	10.2	9.95	10.3	10.8	11.1	11.3	11.1	10.8	10.3	9.87	10.1	10.6	10.9			
20	11.3	11.2	10.7	10.1	9.64	10.2	10.9	11.3	11.5	11.3	10.8	10.2	9.53	9.97	10.6	11.1			
25	11.4	11.3	10.7	9.86	9.24	9.98	10.9	11.5	11.7	11.4	10.8	9.95	9.13	9.73	10.6	11.2			
30	11.5	11.3	10.6	9.56	8.77	9.68	10.8	11.6	11.8	11.5	10.7	9.64	8.63	9.40	10.4	11.2			
35	11.5	11.3	10.4	9.19	8.22	9.32	10.7	11.5	11.9	11.5	10.5	9.25	8.09	9.01	10.2	11.2			
40	11.5	11.2	10.2	8.76	7.62	8.89	10.4	11.4	11.8	11.4	10.3	8.83	7.46	8.56	9.99	11.1			
45	11.4	11.0	9.87	8.29	6.97	8.40	10.1	11.3	11.7	11.3	9.97	8.33	6.81	8.07	9.70	10.9			
50	11.2	10.8	9.51	7.76	6.27	7.88	9.74	11.0	11.5	11.0	9.61	7.79	6.11	7.54	9.34	10.7			
55	10.9	10.5	9.09	7.20	5.55	7.31	9.31	10.7	11.2	10.7	9.18	7.24	5.39	6.97	8.92	10.4			
60	10.6	10.1	8.61	6.60	4.80	6.70	8.81	10.3	10.9	10.3	8.71	6.63	4.65	6.39	8.46	10.0			
65	10.2	9.63	8.09	5.98	4.04	6.05	8.25	9.83	10.5	9.89	8.19	6.00	3.91	5.80	7.96	9.59			
70	9.76	9.16	7.52	5.32	3.28	5.38	7.65	9.32	10.00	9.39	7.62	5.35	3.17	5.16	7.37	9.07			
75	9.15	8.59	6.92	4.66	2.52	4.68	7.02	8.75	9.45	8.82	7.01	4.67	2.43	4.48	6.78	8.52			
80	8.53	7.96	6.29	3.98	1.77	3.96	6.35	8.11	8.82	8.20	6.37	3.98	1.69	3.81	6.15	7.90			
85	7.88	7.28	5.62	3.30	1.03	3.26	5.65	7.42	8.15	7.53	5.69	3.30	0.96	3.13	5.49	7.24			
90	7.29	6.67	4.99	2.67	0.35	2.65	5.10	6.86	7.58	6.98	5.14	2.73	0.32	2.55	4.90	6.66			
95	7.02	6.41	4.79	2.58	0.35	2.58	4.94	6.64	7.32	6.75	4.98	2.66	0.31	2.48	4.72	6.41			
100	6.84	6.25	4.66	2.15	0.35	2.48	4.80	6.45	7.11	6.56	4.85	2.55	0.31	1.60	4.59	6.25			
105	6.58	5.95	4.11	1.83	0.36	2.28	4.62	6.20	6.84	6.31	4.65	2.33	0.32	1.44	4.14	5.96			
110	6.03	5.36	3.75	1.66	0.37	2.02	4.31	5.88	6.51	5.98	4.33	2.06	0.33	1.41	3.22	5.44			
115	5.56	4.96	3.39	1.47	0.37	1.75	3.94	5.45	6.05	5.53	3.94	1.80	0.33	1.37	2.93	4.88			
120	5.09	4.52	3.08	1.28	0.37	1.49	3.52	4.95	5.52	5.03	3.52	1.52	0.34	1.26	2.79	3.98			
125	4.54	4.03	2.66	1.12	0.37	1.20	3.08	4.39	4.92	4.45	3.07	1.23	0.35	1.03	2.40	3.56			
130	3.99	3.55	2.18	0.94	0.37	0.95	2.63	3.81	4.29	3.87	2.63	0.98	0.35	0.85	1.96	3.35			
135	3.43	3.07	1.84	0.77	0.37	0.74	2.19	3.25	3.66	3.29	2.19	0.77	0.36	0.68	1.65	2.82			
140	2.85	2.55	1.42	0.61	0.37	0.56	1.74	2.66	3.04	2.71	1.74	0.59	0.37	0.56	1.34	2.35			
145	2.32	1.84	1.14	0.49	0.37	0.40	1.33	2.11	2.42	2.15	1.31	0.44	0.37	0.46	1.03	1.78			
150	1.85	1.34	0.88	0.40	0.37	0.39	0.96	1.54	1.81	1.58	0.96	0.38	0.38	0.39	0.78	1.33			
155	1.37	0.94	0.66	0.39	0.37	0.39	0.65	1.07	1.18	1.11	0.65	0.38	0.38	0.39	0.58	0.93			
160	0.94	0.65	0.49	0.39	0.37	0.39	0.42	0.67	0.72	0.71	0.41	0.38	0.38	0.39	0.44	0.64			
165	0.57	0.44	0.40	0.39	0.37	0.39	0.40	0.39	0.44	0.42	0.40	0.38	0.38	0.39	0.39	0.45			
170	0.40	0.39	0.40	0.39	0.37	0.39	0.40	0.40	0.39	0.40	0.40	0.38	0.38	0.39	0.39	0.41			
175	0.39	0.39	0.40	0.39	0.37	0.39	0.40	0.40	0.39	0.40	0.40	0.38	0.38	0.39	0.39	0.41			
180	0.39	0.39	0.40	0.39	0.38	0.39	0.40	0.39	0.39	0.40	0.40	0.38	0.38	0.39	0.39	0.40			

C角度范围: 0度 - 360度
C角度间隔: 22.5度
测试速度: 快速
环境温度: 25.3℃
测试人员: Cloud
测试日期: 2024-10-15


γ角度范围: 0度 - 180度
γ角度间隔: 1.0度
测试系统: 远方 (EVERFINE) GO-2000B_V1 系统 V2.00.488
环境湿度: 65.0%
测试距离: 6.360米 [K=1.0000]
备注: RED

I (cd)



1000 lm

$\kappa = 1$



F = 1000 lm
 K = 0.7
 Hcc = 0.8 m
 Hfc = 0.0 m
 Eave = 100 lx

	Pcc	Pw	Pfc
—————	70	50	30
—————	50	30	20

